



	COAXIAL CABLE TRI-LAN-400 50 Ω	RJ-45 PLUG SHIELD RJ45/WP-N*P10
		
	2.79 EUR 2.79 EUR	0.43 EUR 0.43 EUR
In section	100 m . Price for 1m when buying a whole roll	...
In package	...	10 pcs The price for package
Application	...	RJ-45 modular plug shield
Material	...	Rubber
Inner conductor	Ø 2.7 mm Cu ± 0.02 mm Wire	...
Color	...	Blue
Dielectric	Ø 7.2 mm Physical foam	...
Shield	Foil - Al/PET	...
Braid	168 x Ø 0.15 mm Stranded wire CuSn	...
Impedance	50 Ω	...
Outer coating	Ø 10.3 mm ± 0.20 mm PE	...
Main features	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C 	...
Cable attenuation at 100m section	Temperature : 20 °C 2.3 dB @ 30 MHz 3.0 dB @ 50 MHz 4.9 dB @ 150 MHz 6.0 dB @ 220 MHz 8.7 dB @ 450 MHz 12.8 dB @ 900 MHz 17.0 dB @ 1500 MHz 18.8 dB @ 1800 MHz 20.0 dB @ 2000 MHz 22.7 dB @ 2500 MHz 37.6 dB @ 5800 MHz	...

Maximum transmitted power	3.36 kW @ 30 MHz 2.59 kW @ 50 MHz 1.47 kW @ 150 MHz 1.20 kW @ 220 MHz 0.82 kW @ 450 MHz 0.57 kW @ 900 MHz 0.43 kW @ 1500 MHz 0.39 kW @ 1800 MHz 0.36 kW @ 2000 MHz 0.32 kW @ 2500 MHz 0.20 kW @ 5800 MHz	...
Guarantee	2 years	2 years

