



	POWER DISTRIBUTION UNIT ACAR-S8/FA/RACK	THERMOSTAT KTO-011
		
	44.10 CAD 44.10 CAD	8.64 CAD 8.64 CAD
Sensor type	...	Bimetallic
Rated voltage	230 V AC / 50 Hz	...
Contact type	...	NC - opened after exceeding the set temperature
Nominal load current	10 A (total)	...
Maximal power voltage	...	250 V AC
Relay maximal load	...	10 A
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Temperature set range	...	0 °C ... 60 °C
Number of outlets	8 grounded outlets 10A/250V	...
Automatic delayed fuse	✓	...
Hysteresis	...	7 °C \pm 4 °C
Nominal stroke current	2 kA (L/N) - 8/20 μ s	...
Operation temp	...	-20 °C ... 80 °C
Maximum stroke current	6.5 kA (L/N) - 8/20 μ s	...
"Index of Protection"	...	IP20
Leak current	< 0.5 mA	...
Assembly	...	DIN TS-35 rail
Response time	< 25 ns	...
Switch	two-way, with light indication	...
Length of the cable	2.9 m	...
Housing	RACK 19", 1U, Plastic - non-flammable	...
Weight	0.61 kg	0.040 kg
Dimensions	445 x 54 x 55 mm	60 x 43 x 33 mm
Guarantee	2 years	2 years