




	<a href="#">IP CAMERA DS-2CD1343G2-LIU(2.8MM)PL Smart Hybrid Light - 3.7 Mpx Hikvision</a>	<a href="#">CONNECTOR FOR LED STRIPS AD-TL-6499/Z/T/RGBW 12 mm ORNO</a>	<a href="#">ANGULAR PLUG LE-50184 230 V 16 A LEGRAND</a>
			
	165.44 EUR 165.44 EUR	1.28 EUR 1.28 EUR	3.64 EUR 3.64 EUR
Standard	IP	...	...
Rated voltage	...	...	230 V / 50 Hz
Application	...	Works with LED lighting RGBW	...
Maximal current load	...	...	16 A
Strip width	...	12 mm	...
Grounding	...	...	—
Electrical cable	...	...	max. 2 x 1.5 mm <sup>2</sup>
Cable terminals	...	...	screw terminals
Plug type	...	...	CEE 7/17
Maximal power voltage	...	48 V	...
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...	...
Sensor	1/3 " Progressive Scan CMOS	...	...
Lens	2.8 mm	...	...
View angle	98 °	...	...
White light LED illuminator range	30 m	...	...
Range of IR illumination	30 m	...	...
Memory card slot	—	...	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...
Alarm inputs / outputs	—	...	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> <li>• Noise and echo reduction</li> </ul>	...	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 20 fps @ 3.7 Mpx</li> <li>• 25 fps @ 1080p</li> </ul>	...	...
Network interface	10/100 Base-T (RJ-45)	...	...
WEB Server	Built-in	...	...
Max. number of on-line users	6	...	...
ONVIF	✓	...	...

Main features	<ul style="list-style-type: none"> <li>• Smart Hybrid Light technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> </ul>	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>Port no.: 8000 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>	...	...
Default IP address	192.168.1.64	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...
Web browser access ports	80	...	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...	...
Mobile client access ports	8000	...	...
Port ONVIF	80	...	...
RTSP URL	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 420 mA</li> </ul>	...	...
Power consumption	<ul style="list-style-type: none"> <li>• ≤ 6.5 W @ PoE</li> <li>• ≤ 5 W @ 12 V DC</li> </ul>	...	...
Housing	Dome, Metal + Plastic	...	...
Color	White	White	Black
"Index of Protection"	IP67	—	...
Mechanical protection class	—	...	...
Operation temp	-30 °C ... 60 °C	...	...
Weight	0.36 kg	0.002 kg	0.022 kg
Dimensions	Ø 110 x 89 mm	28 x 20 mm	Ø 37 x 49 mm
Supported languages	Polish	...	...
Manufacturer / Brand	Hikvision	ORNO	LEGRAND
SAP Code	311327292	...	...
Guarantee	3 years	2 years	2 years