





	MONITOR DESK MOUNT AX-PIXEL-SINGLE RED EAGLE	EXTENDER ETHERNET+PoE LR1002-1ET TRANSMITTER DAHUA	RELAY MODULE AWZ-520	VIDEO SEPARATOR AHD, HD-CVI, HD-TVI, PAL PFM791 DAHUA
				
	18.01 EUR 18.01 EUR	52.13 EUR 52.13 EUR	12.91 EUR 12.91 EUR	18.41 EUR 18.41 EUR
LAN ports	...	1 pcs RJ45
Number of relay outputs	5	...
Transmission ports	...	1 pcs BNC
Mounting standard	VESA 100 x 100, 75 x 75
Standard	AHD, HD-CVI, HD-TVI, PAL
Transmission speed	...	10 / 100 Mbps Full Duplex
Device type	Passive
Screen size range	13 " ... 27 "
Current consumption	37 mA per each relay at voltage 12 V DC	...
Bearing capacity	8 kg
Number of inputs	1 - BNC socket
Color	Black
Number of outputs	1 - BNC plug
Tilt adjustment	-60 ° ... 60 °
Transmission range	...	max. 1000 m @ 10 Mbps max. 400 m @ 100 Mbps The range of data transfer and power supply is strongly dependent on the cable used and the power required to supply the receiver
Relay maximal load	2 A (max), 30 V DC / 50 V AC (max)	...
Input impedance	75 Ω
Horizontal rotation	360 °
Protections	...	Overvoltage
Output	5 x NO/NC	...
Output impedance	75 Ω
Rotation in the plane of the screen	360 °
Opto-isolation between input and output	800 V - peak
Insertion loss	0.5 dB
Bandwidth	0 ... 65 MHz

Main features	<ul style="list-style-type: none"> • Mount tube length 40 cm • Distance 17 cm in the bolt axis 	<ul style="list-style-type: none"> • Plug & Play • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Support for IP cameras and network devices • Easy installation - doesn't require any configuration of IP nor MAC address • The device operates from the camera side • Possibility to mount on a wall, or on the DIN TS-35 rail • UTP cable length to the camera max. 2 m 	LED indication	<ul style="list-style-type: none"> • Overvoltage protection : 4 kV 10/700 µs • Compliance with IEC61000-4-2, IEC61000-4-5 standards • MTBF (Mean Time Between Faults) > 20000 h • Length of the cables 2 x 13 cm
ESD protection	600 V (contact discharge) 8000 V (air-gap discharge)
Power supply	...	<ul style="list-style-type: none"> • ePoE • PoE (802.3af/at) 	10 ... 14 V DC	—
Housing type	ABS
Operation temp	-10 °C ... 40 °C	-20 °C ... 55 °C
Permissible relative humidity	0 % ... 95 %
Weight	2.07 kg	0.061 kg	0.12 kg	0.034 kg
Dimensions	515 x 262 x 117 mm	79 x 64 x 23 mm	140 x 43 x 23 mm	42 x 23 x 16 mm
Manufacturer / Brand	RED EAGLE	DAHUA	PULSAR	DAHUA
Guarantee	2 years	3 years	2 years	3 years

