

	RJ45 CONNECTOR TOOL KIT NS-468/KIT	IP CAMERA IPC-HFW1431T-ZS-2812-S4 - 4 Mpx 2.8 ... 12 mm - MOTOZOOM DAHUA
		
	11.01 EUR 11.01 EUR	303.47 EUR 303.47 EUR
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Tested cables	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C), RJ12 (6P6C)	...
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	2.8 ... 12 mm - Motozoom
Application	Plug RJ45 (8P8C) , Plug RJ12 (6P6C) , Plug RJ11 (6P4C) / DEC	...
View angle	...	<ul style="list-style-type: none"> • 98 ° ... 31 ° (manufacturer data) • 92 ° ... 31 ° (our tests result)
Compression	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	...	50 m
Alarm inputs / outputs	...	—
Main stream frame rate	...	20 fps @ 4 Mpx 25 fps @ 3.7 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, HTTPS, TCP, ARP, RTSP, RTP, UDP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, IEEE 802.1x
Audio	...	—
WEB Server	...	Built-in
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Max. number of on-line users	...	20
ONVIF	...	18.12
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.108
Web browser access ports	...	80, 37777

PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
RS-485 interface	...	—
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Motion Detection - max. 4 zones • Privacy zones - max. 4 • Auto White Balance • Mirror - Horizontal mirror image
Power supply	Battery 9 V 6LR61 (not included)	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 620 mA
Power consumption	...	< 7.4 W
Housing	...	Compact, Metal
Color	...	White
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Italian
Weight	0.12 kg 0.77 kg (total)	0.84 kg
Dimensions	101 x 107 x 28 mm 260 x 170 55 mm (case)	244 x 90 x 90 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00