







	<a href="#">PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412302 1+2 TYPE 50 kA LEGRAND</a>	<a href="#">ACCESS POINT +ROUTER ACB-ISP Wi-Fi 2.4 GHz 300 Mbps UBIQUITI</a>	<a href="#">ELECTRIC CABLE YKY-5X6.0</a>	<a href="#">POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m</a>	<a href="#">ACCESS CONTROLLER DS-K2602T Hikvision</a>
					
	48.51 EUR 48.51 EUR	37.93 EUR 37.93 EUR	5.49 EUR 5.49 EUR	3.71 EUR 3.71 EUR	596.75 EUR 596.75 EUR
Frequency range	...	2.4 GHz	...	...	...
Antenna type	...	2x2 MIMO - built-in 4 dBi	...	...	...
Maximal voltage	320 V AC, 50 / 60 Hz	...	...	...	...
Total maximal current	...	...	...	10 A	...
In section	...	...	<b>100 m . Price for 1m when buying a whole roll</b>	...	...
Number of supported readers	...	...	...	...	• 4 pcs @ RS-485, • 4 pcs @ Wiegand
Maximal total load	...	...	...	2500 W	...
Battery backup support	...	...	...	...	max. 7 Ah
Number of outlets	...	...	...	4 grounded outlets 10A/250V CEE 7/5	...
Standards	...	IEEE 802.11n, Wi-Fi	...	...	...
Class	1+2 type ( Class B+C )	...	...	...	...
Fuse	...	...	...	—	...
Inner conductor	...	...	5 x 6.0 mm <sup>2</sup> - Cu wire	...	...
Baud rates	...	300 Mbps	...	...	...
Rated voltage	230 / 400 V AC, 50 / 60 Hz	...	0.6 / 1 kV	220 ... 240 V AC / 50 Hz	...
Switch	...	...	...	—	...
Protections	...	WPA2	...	...	...
Wire gauge	...	...	...	3 x 1.5 mm <sup>2</sup>	...
Outer coating	...	...	Ø 17.2 mm - PVC	...	...
Length of the cable	...	...	...	1.3 m	...
Coating color	...	...	Black	...	...
LAN ports	...	4 x 10/100 Mbps	...	...	...
Protection level Up	1.2 kV @ 10/350 µs (T1) 1.7 kV @ 8/20 µs (T2)	...	...	...	...
Color	...	...	...	Black	...
Transmitter power	...	19 dBm (max)	...	...	...
Power supply PoE	...	Ubiquiti Passive PoE	...	...	...
Nominal discharge current	8 kA @ 10/350 µs (T1) 20 kA @ 8/20 µs (T2)	...	...	...	...
Input lines	...	...	...	...	• 4 pcs - Alarm inputs, • 2 pcs - Reed switch , • 2 pcs - Door/gate opening button, • 5 pcs - Tamper
Maximum stroke current	50 kA @ 8/20 µs (T2)	...	...	...	...
Operation state indication	✓	...	...	...	...
Housing	Plastic	...	...	Plastic	...
Output lines	...	...	...	...	• 2 pcs - Lock relay, • 4 pcs - Relay
Power consumption	...	≤ 5 W	...	...	...
Communication	...	...	...	...	• RS-485, • Ethernet, • Wiegand (w26 / w34), • Open Supervised Device Protocol (OSDP)

Power supply	...	• 4.95 ... 5.05 V DC / 2 A - micro USB socket (power adapter not included) • PoE 24 V - Port 1	...	...	100 ... 240 V AC
Main features	Varistor	• PoE OUT 24 V - port WAN, (4, 5+; 7, 8-) • Port Security : Contact/Air (ESD/EMP) $\pm$ 24 kV / $\pm$ 24 kV • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network	...	...	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 300000 events</li> <li>• Remote programming from PC</li> <li>• Metal housing</li> </ul>
Operation temp	...	-10 °C ... 50 °C	...	...	-20 °C ... 65 °C
Permissible relative humidity	...	5 % ... 95 %	...	...	10 % ... 90 % (non-condensing)
Weight	0.098 kg	0.22 kg	...	0.26 kg	4.6 kg
Dimensions	62 x 54 x 17 mm	89 x 90 x 89 mm	...	196 x 54 x 39 mm	373 x 345 x 98 mm
Manufacturer / Brand	LEGRAND	UBIQUITI	...	...	Hikvision
SAP Code	...	...	...	...	302913795
Guarantee	2 years	2 years	2 years	2 years	3 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00