



	IP CAMERA IPC3614LE-ADF28K-G - 4 Mpx 2.8 mm UNIVIEW	TIME & ATTENDANCE RECORDER ASA3213G-MW DAHUA
		
	153.51 EUR 153.51 EUR	477.85 EUR 477.85 EUR
Sensor	1/3 " Progressive Scan CMOS	CMOS
Matrix size	4 Mpx	2 Mpx
Scanning system	Progressive	...
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p	1920 x 1080 - 1080p
Standard	TCP/IP	TCP/IP
Lens	2.8 mm	...
IR illuminator	...	✓
LED illuminator	...	✓
Temperature measurement	...	—
View angle	• 101 ° (manufacturer data) • 96 ° (our tests result)	...
Temperature measurement range	...	—
Range of IR illumination	30 m	...
Accuracy of temperature measurement	...	—
S/N ratio	> 52 dB	...
Face recognition distance	...	0.3 m ... 1.5 m (max 500 faces in the database)
RFID proximity reader built-in	...	• 13.56 MHz S50 • Memory of 500 RFID cards
Internal memory	...	Support storage of 150 000 records
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	...
Video output	...	—
RS-485 interface	—	✓
RS-232 interface	...	—
Wiegand interface	...	—
USB	...	1 x USB 2.0
Main stream frame rate	25 fps @ 3.7 Mpx	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	—
Alarm inputs / outputs	—	1 / 1 - Relay outputs

Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network • Audio detection 	Voice message
Network interface	10/100 Base-T (RJ-45)	1 x 10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP	IPv4, RTSP, RTP, TCP, UDP, P2P
WEB Server	Built-in	Built-in
Max. number of on-line users	32	...
ONVIF	✓	—
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	DHCP or 192.168.1.13	192.168.1.108
Default admin user / password	admin / 123456	admin / - The administrator password should be set at the first start
Web browser access ports	80, 554	80, 37777
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	37777
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...

Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette) 	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera - 4.3 " capacitive touch screen, 480 x 272 px • Identification modes : PIN, Proximity identifier 13.56 MHz S50, Face recognition, Any combination of the above • 500 users • Software update via network • Real-time Surveillance • Multiple Authentication • Take face image after swiping card • Auto-Registration • Recording of information about Time&Attendance • Statistical Reporting • Backup to USB drive (pendrive, external drive) • Output button support • Door status detection • Lock control • Tamper protections
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA 	12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 6 W	≤ 18 W
Housing	Dome, Metal + Plastic	Plastic (ABS)
Color	White	Black + Silver
"Index of Protection"	IP67	—
Vandal-proof	—	...
Operation temp	-30 °C ... 60 °C	-10 °C ... 55 °C
Weight	0.37 kg	<ul style="list-style-type: none"> • 0.22 kg (without stand) • 0.24 kg (with stand)
Dimensions	Ø 118 x 95 mm	<ul style="list-style-type: none"> • 116 x 107 x 22 mm (without stand) • 116 x 107 x 78 mm (with stand)
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian	English
Manufacturer / Brand	UNIVIEW	DAHUA
Guarantee	3 years	3 years