

	TWILIGHT SWITCH FOR LED LIGHTING TWILIGHT-SWITCH/BLEBOX 12 ... 24 V DC	PROBE FOR FLOODING WITH WATER FPX-1-BR FOR THE AXD-200 UNIVERSAL DETECTOR SATEL	POWER DISTRIBUTION UNIT ACAR-P7 (5 + 2 OUTLETS)
			
	32.18 PLN 32.18 PLN	19.00 PLN 19.00 PLN	67.25 PLN 67.25 PLN
Detection	...	Water	...
Length of the sensor cable	...	3 m	...
Sensitivity adjustment	...	—	...
Application	Works with LED lighting - 12-24V LED strips
Alarm signaling	...	—	...
Relay contacts rating (resistive load)	...	—	...
Rated voltage	12 ... 24 V DC	...	230 V AC / 50 Hz
Response time	< 25 ns
Power supply	...	—	...
Maximal total load	60 ... 120 W	...	2300 W
Number of outlets	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V
Total maximal current	5 A	...	10 A
Number of inputs	0
Automatic delayed fuse	10 A / 250 V
Number of outputs	1
Leak current	< 0.5 mA
Connector type	PCB (soldering)
Nominal voltage of surge suppressor	250 V / 50 Hz
Wireless	—
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Mobile phones support	—
Nominal stroke current	2 kA (L/N) - (8/20μs)
Switch	two-way, with light indication
Maximum stroke current	6.5 kA (L/N) - (8/20μs)
Length of the cable	1.45 m

Main features	<ul style="list-style-type: none"> • High power - max. 120 W, • Automatic calibration, • Mild lightening at dusk, • Mild darkening at dawn, • Small dimensions, • Possible assembly in a profile 	<ul style="list-style-type: none"> • detecting the presence of water in spaces where there is a risk of leakage 	...
Housing	—	...	Plastic - non-flammable
"Index of Protection"	—
Color	—	Brown	...
Operation temp	-20 °C ... 50 °C
Weight	0.001 kg	0.05 kg	0.44 kg
Dimensions	34 x 8.5 x 4 mm	34 x 14 x 7.5 mm	370 x 65 x 44 mm
Manufacturer / Brand	BleBox	SATEL	...
Guarantee	2 years	2 years	2 years