





	<a href="#">VIDEO SEPARATOR D-SEP2/HD</a>	<a href="#">TV OR MONITOR MOUNT AX-HAMMER</a>	<a href="#">SPEAKER CABLE HI-FI/2X0.5</a>	<a href="#">AUTOMATIC TRANSFER SWITCH DY-ATS-14020SDA Dynamo</a>
				
	6.12 EUR 6.12 EUR	27.35 EUR 27.35 EUR	0.31 EUR 0.31 EUR	212.36 EUR 212.36 EUR
Support	...	...	...	DY-14020SDA
Maximum power	...	...	...	10 kW
In section	...	...	<b>100 m . Price for 1m when buying a whole roll</b>	...
Nominal power	...	...	...	• 3.5 kW @ 230 V, • 10 kW @ 400 V
Inner conductor	...	...	2 x Ø 0.5 mm Cu-OFC Stranded wire	...
Mounting standard	...	VESA 75, 100, 200, 200 x 100, 300, 400 x 200, 400, 600 x 400	...	...
Outer coating	...	...	PVC	...
Coating color	...	...	Colorless	...
Screen size range	...	23 " ... 70 "	...	...
Standard	• AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx, 4K UHD • CVBS - PAL / NTSC	...	...	...
Bearing capacity	...	50 kg	...	...
Device type	Passive	...	...	...
Maximal current	...	...	...	• 15.2 A @ 230 V, • 26.3 A @ 400 V
Number of inputs	1 pcs BNC socket	...	...	...
Battery charging current	...	...	...	3 A
Distance from mounting surface	...	83 ... 455 mm	...	...
Number of outputs	1 pcs BNC plug	...	...	...
Isolation class	...	...	...	F
Color	...	Black	...	...
Input impedance	75 Ω	...	...	...
"Index of Protection"	...	...	...	IP 41
Output impedance	75 Ω	...	...	...
Tilt adjustment	...	0 ° ... 15 °	...	...
Opto-isolation between inputs and outputs	16 V DC	...	...	...
Operation temp. / Relative humidity	...	...	...	0 ... 40 °C / ≤ 95 %
Horizontal rotation	...	-45 ° ... 45 °	...	...
Rotation in the plane of the screen	...	—	...	...
Manufacturer / Brand	...	...	...	Dynamo

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Attenuation	<ul style="list-style-type: none"> <li>• 4.43 MHz @ 0.21 dB</li> <li>• 11 MHz @ 0.41 dB</li> <li>• 21 MHz @ 0.82 dB</li> <li>• 38 MHz @ 1.19 dB</li> <li>• 42 MHz @ 1.17 dB</li> <li>• 67.5 MHz @ 3.46 dB</li> </ul>	...	...	...
Insertion loss	0.5 dB	...	...	...
Bandwidth	180 MHz	...	...	...
Power supply	—	...	...	...
Operation temp	-20 °C ... 55 °C	...	...	...
Weight	0.03 kg	4.8 kg	...	5.2 kg
Dimensions	60 x 28 x 22 mm	670 x 430 x (83 ... 455) mm	...	250 x 320 x 152 mm
Guarantee	2 years	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00