




	<a href="#">RED CHALK POWDER ST-1-47-404 STANLEY</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1231TM- 18-A-0360B - 1080p 3.6 mm DAHUA</a>	<a href="#">IP CAMERA TC-C34WP SPEC:W/E/Y/2.8MM/V4.0 Color Maker 2.8 mm TIANDY</a>
			
	2.07 EUR 2.07 EUR	103.85 EUR 103.85 EUR	191.11 EUR 191.11 EUR
Application	<ul style="list-style-type: none"> <li>• For use in masonry work,</li> <li>• Electrical works, such as marking lines for pipes, trays or lines for lighting lamps</li> </ul>	...	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS	IP
Waterproof	✓	...	...
Net weight	115 g	...	...
Matrix size	...	2.1 Mpx	...
Resolution	...	1920 x 1080 - 1080p 960 x 576 - 960H, PAL	2592 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	...	1/2.8 " CMOS	1/2.8 " Progressive Scan CMOS
Range of IR illumination	...	80 m	...
Lens	...	3.6 mm	2.8 mm
IR illuminator power adjustment	...	Automatic	...
View angle	...	<ul style="list-style-type: none"> <li>• 86 ° (manufacturer data)</li> <li>• 82 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 100 ° (manufacturer data)</li> <li>• 90 ° (our tests result)</li> </ul>
White light LED illuminator range	...	...	15 m
Memory card slot	...	...	Micro SD card support up to 512GB
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Image compression method	...	...	S+265 / H.265 / H.264
S/N ratio	...	> 65 dB	...
Alarm inputs / outputs	...	...	—
OSD menu	...	✓	...
Audio	...	Microphone built-in, HD-CVI only	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> </ul>
Main stream frame rate	...	...	25 fps @ 4 Mpx
Interface	...	...	10/100 Base-TX (RJ-45)
WEB Server	...	...	Built-in

Max. number of on-line users	...	...	2
ONVIF	...	...	✓
Mobile phones support	...	...	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>
Access from PC	...	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Default IP address	...	...	DHCP or 192.168.1.2
Default admin user / password	...	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	...	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	...	3000, 3001
PC client access ports	...	...	3000, 3001
Port ONVIF	...	...	80
Intelligent image analysis	...	...	<ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• intrusion</li> <li>• video tampering</li> </ul>



Main features	...	<ul style="list-style-type: none"> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• AGC - Automatic Gain Control</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Color maker - colorful night mode</li> <li>• Motion Detection</li> </ul>
Power supply	...	12 V DC / 430 mA	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 590 mA</li> </ul>
Power consumption	...	≤ 5.1 W	≤ 7 W
Housing	...	Compact, Metal	Compact - Metal + Plastic
Color	Red	White	White
"Index of Protection"	...	IP67	IP67
Mechanical protection class	...	...	—
Operation temp	...	-40 °C ... 60 °C	-40 °C ... 65 °C
Weight	...	0.65 kg	0.3 kg
Dimensions	...	241 x 91 x 90 mm	160 x 73 x 73 mm
Supported languages	...	...	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	STANLEY	DAHUA	TIANDY
Guarantee	2 years	3 years	3 years