




	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1200TL-A-0360B-S5 - 1080p 3.6 mm DAHUA</a>	<a href="#">MAST BASE MF-55</a>	<a href="#">COAXIAL CABLE TRI-LAN-240 50 Ω</a>
			
	71.56 EUR 71.56 EUR	2.53 EUR 2.53 EUR	0.94 EUR 0.94 EUR
Mast diameter	...	max. Ø 55 mm	...
Material	...	Metal	...
In section	...	...	<b>100 m . Price for 1m when buying a whole roll</b>
Standard	AHD, HD-CVI, HD-TVI, CVBS	...	...
Sensor	1/2.7 " CMOS	...	...
Mounting holes	...	2 x Ø 8 mm	...
Inner conductor	...	...	Ø 1.4 mm Cu ± 0.02 mm Wire
Matrix size	2.1 Mpx	...	...
Dielectric	...	...	Ø 3.8 mm Physical foam
Shield	...	...	Foil - Al/PET/Al
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	...	...
Lens	3.6 mm	...	...
Braid	...	...	112 x Ø 0.12 mm Stranded wire CuSn
Impedance	...	...	50 Ω
Outer coating	...	...	Ø 6.1 mm ± 0.02 mm PE
View angle	• 88 ° (manufacturer data) • 86 ° (our tests result)	...	...
Range of IR illumination	80 m	...	...
IR illuminator power adjustment	Automatic	...	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...	...
Main features	...	The whole galvanized	<ul style="list-style-type: none"> <li>• low attenuation</li> <li>• perfect matched</li> <li>• high screening efficiency</li> <li>• it can be used in WLAN 2,4GHz and 5GHz installations</li> <li>• Operation temp : -40 °C ... 70 °C</li> <li>• Minimal bend radius : 30 / 60 mm</li> </ul>

Audio	Microphone built-in, HD-CVI only	...	...
S/N ratio	> 65 dB	...	...
OSD menu	✓	...	...
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Sharpness - sharper image outlines</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> </ul>	...	...
Power supply	12 V DC / 440 mA	...	...
Power consumption	≤ 5.3 W	...	...
Housing	Compact, Plastic / Metal	...	...
Color	White	...	...
"Index of Protection"	IP67	...	...
Operation temp	-40 °C ... 60 °C	...	...
Weight	0.28 kg	...	...
Dimensions	80 x 75 x 199 mm	...	...
Cable attenuation at 100m section	...	...	Temperature : 20 °C 4.2 dB @ 30 MHz 5.4 dB @ 50 MHz 9.2 dB @ 150 MHz 11.2 dB @ 220 MHz 16.2 dB @ 450 MHz 23.3 dB @ 900 MHz 30.7 dB @ 1500 MHz 33.9 dB @ 1800 MHz 35.9 dB @ 2000 MHz 40.6 dB @ 2500 MHz 65.2 dB @ 5800 MHz
Manufacturer / Brand	DAHUA	DELTA	...

Maximum transmitted power	...	...	1.41 kW @ 30 MHz 1.09 kW @ 50 MHz 0.62 kW @ 150 MHz 0.51 kW @ 220 MHz 0.35 kW @ 450 MHz 0.24 kW @ 900 MHz 0.19 kW @ 1500 MHz 0.17 kW @ 1800 MHz 0.16 kW @ 2000 MHz 0.14 kW @ 2500 MHz 0.09 kW @ 5800 MHz
Guarantee	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00