



	POWER SUPPLY ADAPTER RACK ZR12-100/G-8-UHD 12 V DC 8.5 A	SMART LED LIGHTING CONTROLLER SLW-02 Wi-Fi, 12 ... 24 V DC ZAMEL
		
	850.41 NOK 850.41 NOK	505.78 NOK 505.78 NOK
Adapter type	Switching	...
Support	...	SUPLA
Application	...	Works with LED lighting - single-color (MONO) 12-24V LED strips
Rated voltage	...	12 ... 24 V DC
Power voltage	selectable by switch • 90 V ... 132 V AC, • 180 V ... 264 V AC	...
Maximal total load	...	140 W
Output voltage	12 V DC	...
Output voltage adjustment	11.4 ... 13.2 V	...
Maximal load	8.5 A	...
Total maximal current	...	6 A (2 A / Channel)
Maximal current for single output	1 A	...
Output power	102 W	...
Protections	• Short-circuit • Overload • Overvoltage • Temperature	...
MTBF (Mean Time Between Faults)	> 700000 h	...
Maximal outputs load	...	LED 12 V : 5 m - 70 W LED 24 V : 10 m - 140 W
Number of video outputs	8 pcs BNC socket	...
Number of inputs	...	1
Number of video inputs	8 pcs screw terminals	...
Number of outputs	...	3
Connector type	...	screw terminals
Number of power outputs	8 pcs Cable terminals	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	...	• The SUPLA free application on Android • The SUPLA free application on iOS

Standard	<ul style="list-style-type: none"> • AHD - 8 Mpx 4K UHD • HD-CVI - 8 Mpx 4K UHD • HD-TVI - 8 Mpx 4K UHD • CVBS - PAL / NTSC 	...
Type of fuses	8 x 1A/250V, 5/20mm, delayed	...
LEDs application	<ul style="list-style-type: none"> • red "POWER" - indicates the power voltage (DC IN) • green "PWR LED" - indicates the fuse blown (if there is no light means the fuse blown) 	...
Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • remote access, • voice control
"Index of Protection"	...	IP20
Max. current	<ul style="list-style-type: none"> • 150mA camera - 98 meters (R=3,4Ohm/100m) • 150mA camera - 60 meters (R=5,5Ohm/100m) • 650mA camera + thermostat - 22 meters (R=3,4Ohm/100m) • 650mA camera + thermostat - 14 meters (R=5,5Ohm/100m) 	...
Assembly	Rack 19"	...
Housing	Metal	Plastic
Operation temp	...	-20 °C ... 50 °C
Color	Black	Green
Operation temp. / Relative humidity	-10 °C ... 55 °C / < 95 %	...
Weight	0.69 kg	0.030 kg
Dimensions	483 x 44 x 122 mm	47 x 47 x 20 mm
Manufacturer / Brand	DELTA	ZAMEL
Guarantee	5 years	2 years