




	<a href="#">WIRELESS PANIC BUTTON ARD822-W2(868)(STRAP) DAHUA</a>	<a href="#">POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-9-11-F 9-PORT ATTE</a>	<a href="#">BOX POSITIONER PDP/EPN Elektro-Plast</a>	<a href="#">DUAL SMART SWITCH SWITCHBOX-D/BLEBOX Wi- Fi, 230 V AC</a>	<a href="#">DIGITAL TIMER OR- PRE-409.ORNQ</a>
					
	375.73 SEK 375.73 SEK	2721.96 SEK 2721.96 SEK	108.07 SEK 108.07 SEK	427.69 SEK 427.69 SEK	156.92 SEK 156.92 SEK
Support	Wireless alarm systems DAHUA	...	...	...	...
Application	...	...	Marking holes for Ø68 mm multiple boxes	switching devices on/off	...
Device type	...	...	...	...	Digital timer
Frequency band	868 MHz	...	...	...	...
Rated voltage	...	...	...	230 V AC	...
Maximal current	...	...	...	...	16 A
Radio communication range (at open area)	max. 1400 m (open area)	...	...	...	...
Maximal load	...	...	...	...	3680 W
Number of buttons	2	...	...	...	...
Maximal total load	...	...	...	2 x 1150 W / 1150 VA	...
Measuring accuracy	...	...	...	...	≤ 1 minute / month
Total maximal current	...	...	...	2 x 5 A	...
LAN ports	...	• 1 x RJ45 10/100 Base-T - Uplink, • 9 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE	...	...	...
Number of inputs	...	...	...	2	...
Material	...	...	Plastic	...	...
Timing range	...	...	...	...	1 minute ... 168 hours (7 days)
Number of outputs	...	...	...	2	...
Connector type	...	...	...	screw terminals	...
Management	...	—	...	...	...
The maximum countdown time	...	...	...	...	99 hours 59 minutes
Wireless	...	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Battery lifetime	~ 5 years	...	...	...	...
Mobile phones support	...	...	...	• The <a href="#">wBox</a> free application on Android • The <a href="#">wBox</a> free application on iOS	...
LED diodes	...	AC, DC, CHARGING (battery charging), PoE	...	...	...
Permissible relative humidity	10 % ... 90 %	...	...	...	...
Transmission speed	...	• 10 / 100 Mbps : 1 x Port Uplink, • 10 / 100 Mbps : 9 x Port LAN & PoE	...	...	...
Security class	...	...	...	...	IP20
Socket type	...	...	...	...	2P+Z, E type
Housing	...	...	...	Plastic	Plastic
"Index of Protection"	...	...	...	IP20	...
Operation voltage	...	...	...	...	175 ... 276 V AC, 45 ... 65 Hz
Color	...	...	...	Black	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Maximal output power	...	<ul style="list-style-type: none"> <li>• 40 W @ Passive PoE - LAN1 ... LAN4 ports,</li> <li>• 60 W @ Passive PoE - Port LAN5,</li> <li>• 30 W @ PoE (802.3af/at) - LAN1 ... LAN5 ports</li> </ul>	...	...	...
Operation temp	...	...	...	...	0 °C ... 50 °C
Operation temp	-10 °C ... 55 °C	...	...	-20 °C ... 50 °C	...
Maximal total power	...	60 W	...	...	...
Operation modes	...	<ul style="list-style-type: none"> <li>• Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN6 ports</li> <li>• Long Range : 280 m @ 10 Mb/s - LAN1 ... LAN4 ports ; 100 m @ 10/100 Mb/s - LAN5, LAN6 ports</li> </ul>	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Bidirectional communication</li> <li>• AES128 data encryption</li> <li>• LED indication</li> <li>• Frequency hopping against jamming for reliable transmission</li> <li>• Lanyard included</li> <li>• "Index of Protection" : IP54</li> </ul>	<ul style="list-style-type: none"> <li>• The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 9 ports</li> <li>• The modular design streamlines service tasks and enables quick and easy system expansion</li> <li>• The raster system of module assembly facilitates the expansion of the device by further modules</li> <li>• Place for battery : 12 V / 18 Ah</li> <li>• Battery charging current : 1 A / 2 A - (set with the JP1 jumper)</li> <li>• Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery</li> <li>• Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF)</li> <li>• PSU thermal protection : 130 °C</li> <li>• Overload protection</li> <li>• LAN &amp; PoE ports - Short-circuit protection, Overvoltage</li> <li>• TAMPER switch indicating open the cover</li> <li>• "Index of Protection" : IP20</li> </ul>	<ul style="list-style-type: none"> <li>• Can be used in both horizontal and vertical orientation,</li> <li>• Built-in tube levels,</li> <li>• Mounting holes distance : 71 mm</li> </ul>	<ul style="list-style-type: none"> <li>• Local control by physical button,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• The ability to set the default status of the device after a power failure,</li> <li>• µWiFi technology support</li> </ul>	<ul style="list-style-type: none"> <li>• Time settings for switching electrical devices on and off</li> <li>• 16 programs</li> <li>• Manual or random on / off</li> <li>• 16 weekday combinations</li> <li>• Daylight saving (summer) and winter time function</li> <li>• 12 or 24 hour mode</li> <li>• Count down function</li> <li>• Large, readable LCD display</li> <li>• built-in battery</li> </ul>
Power supply	1 x battery CR2032 3V (included)	190 ... 260 V AC	...	...	<ul style="list-style-type: none"> <li>• 230 V AC, 50 Hz</li> <li>• built-in battery</li> </ul>
Weight	0.02 kg	2.48 kg	0.04 kg	0.04 kg	0.15 kg
Dimensions	55 x 36 x 15 mm	325 x 305 x 100 mm	210 x 68 x 21 mm	41 x 39 x 23 mm	115 x 55 x 78 mm
Manufacturer / Brand	DAHUA	ATTE	Elektro-Plast Nasielsk	BleBox	ORNO
Guarantee	2 years	3 years	2 years	2 years	2 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00