




	FLUSH BOX PK-60/K-G/SG/EPN Elektro-Plast	ANGULAR PLUG LE-50107 230 V 16 A LEGRAND	COMPRESSION PLUG BNC-W/4879*P10 RG6 NS100 Triset113
			
	0.90 EUR 0.90 EUR	3.97 EUR 3.97 EUR	6.54 EUR 6.54 EUR
Number of sections	1
Rated voltage	...	230 V / 50 Hz	...
"Index of Protection"	—
Maximal current load	...	16 A	...
In package	10 pcs The price for package
Grounding	...	✓	...
Electrical cable	...	max. 3 x 2.5 mm ²	...
Connector type	BNC Plug
Cable terminals	...	screw terminals	...
Plug type	...	CEE 7/6	...
Attachment of connector elements	Compression mounting
Application	Coaxial cable
Wire mounting	Pressing
Dielectric diameter	max. 4.8 mm
Material	halogen free and inflammable
Cable diameter	max. 7.9 mm
Color	Yellow	Black	...
Shield fastening	Compression mounting
Watertightness	✓
Montage hole diameter	Ø 68 mm
Example of application	<ul style="list-style-type: none"> • RG6, • NS100-TRISHIELD • Triset113
Manufacturer / Brand	Elektro-Plast	LEGRAND	...

Main features	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 850 °C flammability index • 2 special screws with holders to fastening to the wall - included 	...	<ul style="list-style-type: none"> • Properly compressed connection is highly resistant to break • Watertightness of connector with cable connection • Very easy and quick assembly • Corrosion resistance • Very low loss in the whole operating band • To crimp use the crimping tool HT-5082R
Weight	0.024 kg	0.032 kg	0.013 kg
Dimensions	Ø 60 x 47 mm - Internal dimensions Ø 67 x 48 mm - External dimensions	84 x 43 x 37 mm	Ø 14.5 mm x 39 mm
Guarantee	2 years	2 years	2 years