




	CABLE N-W/N-W+RF5-5M	POWER SUPPLY ADAPTER 12V/3A/5.5	IP CAMERA BCS-L-TIP14FSR3-W Wi-Fi - 3.7 Mpx 2.8 mm BCS Line
			
	12.75 EUR 12.75 EUR	8.35 EUR 8.35 EUR	157.45 EUR 157.45 EUR
Standard	TCP/IP
Model identifier	...	12V/3A/5.5	...
Sensor	1/3 " Progressive Scan CMOS
Input voltage	...	100 - 240 V AC	...
Matrix size	3.7 Mpx
AC input frequency	...	50 / 60 Hz	...
Cable	RF-5 : "N" Plug / "N" Plug
Output voltage	...	12.0 V DC	...
Impedance	50 Ω
Output current	...	3.0 A	...
Length of the cable	5 m
Output power	...	36.0 W	...
Average efficiency during work	...	87.4 %	...
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance
Efficiency at low load (10%)	...	81.0 %	...
No-load power consumption	...	< 0.10 W	...
Adapter type	...	Switching	...
Output voltage adjustment	...	—	...
Protections	...	Overload	...
Number of outputs	...	1 pcs	...
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Power connectors type	...	<ul style="list-style-type: none"> • 230 V CEE 7/16 • 12 V - 2.1/5.5 mm Straight plug 	...
Housing type	...	Desktop	...
Lens	2.8 mm, F2.0
View angle	<ul style="list-style-type: none"> • 90 ° (manufacturer data) • 89 ° (our tests result)
Range of IR illumination	30 m
Image compression method	H.265+ / H.265 / H.264+ / H.264
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> • Microphone built-in • Noise reduction • Audio detection
Main stream frame rate	<ul style="list-style-type: none"> • 20 fps @ 3.7 Mpx • 25 fps @ 3 Mpx
Network interface	10/100 Base-T (RJ-45), 2.4 GHz Wi-Fi IEEE 802.11 b/g/n
Network protocols	IPv4, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, DHCP, DNS, NTP, Multicast, RTMP
WEB Server	Built-in, NVR compliance, 20 on-line users
ONVIF	21.06
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Access by a cloud (P2P) • Android: Free application BCS Manager • iOS (iPhone): Free application BCS Manager
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	DHCP
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> • Wi-Fi Module - 2.4 GHz IEEE 802.11 b/g/n ; Antenna - SMA socket • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • D-ZOOM - Digital Zoom 16 x • Mirror - Mirror image • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Configurable Privacy Zones • Motion Detection • Human detection
Housing	Compact - Metal
Color	White
"Index of Protection"	IP67
Power supply	12 V DC / 350 mA
Power consumption	max. 4.1 W
Operation temp	-40 °C ... 60 °C
Weight	0.21 kg	0.26 kg	0.48 kg
Dimensions	...	110 x 50 x 30 mm	Ø 70 x 166 mm
Supported languages	Polish, English
Manufacturer / Brand	BCS Line
Guarantee	2 years	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00