



	<a href="#">FUSE LINK ETI-D01/4A 4 A 400 V gL/gG E14 ETI</a>	<a href="#">AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR BCS-L- XVR0401-VI 4 CHANNELS</a>	<a href="#">RFID PROXIMITY CARD KT- STD-1 SATEL</a>
			
	1.07 EUR 1.07 EUR	147.68 EUR 147.68 EUR	1.92 EUR 1.92 EUR
Standard	...	...	Unique EM 125kHz
Rated current	4 A	...	...
Compatibility	...	...	EM4100/4102
Possibility of programming the serial number (ID)	...	...	—
Ability to write to internal memory	...	...	—
Serial Number overprint	...	...	✓
Standard	...	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Rated voltage	250 V DC, 400 V AC	...	...
Video inputs	...	4 pcs BNC	...
Fusing characteristics	gL/gG	...	...
Fuse base	E14	...	...
Type	D0	...	...
Video outputs	...	1 pcs HDMI 1 pcs VGA	...
Size	D01	...	...
Audio inputs	...	1 pcs CINCH	...
Audio outputs	...	1 pcs CINCH	...
Breaking capacity	50 kA AC, 8 kA DC	...	...
Image compression method	...	AI Coding / H.265+ / H.265 / H.264+ / H.264	...
Main features	<ul style="list-style-type: none"> <li>• Low power and energy losses</li> <li>• Small temperature increase</li> <li>• High ability to limit short-circuit current</li> <li>• Stability of current-time characteristics and full selectivity of operation</li> <li>• Selective cooperation with over-current circuit breakers</li> </ul>	...	...
Housing	Ceramic	...	...

Image records resolutions	...	<ul style="list-style-type: none"> <li>• AHD / HD-CVI / HD-TVI : 5M-N 1296 x 1944 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720</li> <li>• CVBS : 960H - 960 x 576 ,</li> <li>• IP : max. 6 Mpx - 3072 x 2048</li> </ul>	...
Recording speed adjustment	...	6 Mpx IP @ 1 ... 25 fps 5M-N @ 1 ... 10 fps - Channel 1 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 720p @ 1 ... 25 fps 1080N @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel	...
Operation modes	...	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP	...
Recording modes	...	Manual, Motion Detection, Schedule	...
Supported hard drives	...	1 x 6 TB SATA	...
External storage devices backup	...	Save single frames and whole records from DVR drive to the USB drive	...
Searching and playback the records	...	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)	...
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
USB	...	2 x USB 2.0	...
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BCS Manager</a></li> <li>• iOS (iPhone): Free application <a href="#">BCS Manager</a></li> </ul>	...

Alarm inputs / outputs	...	—	...
PTZ control	...	RS-485 - PELCO-D/P and others	...
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Main features	...	Intelligent image analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, abandoned/missing object, face detection, • SMD PLUS - searching for an object classified as: human, motor vehicle, non- motor vehicle - 4 Channels	...
Power supply	...	12 V DC / 1.5 A (power adapter included)	...
Color	...	Black	...
Weight	0.0059 kg	0.87 kg	0.006 kg
Dimensions	Ø 11 x 36 mm Ø 7.3 mm (A)	260 x 236 x 47 mm	86 x 54 x 1 mm
Supported languages	...	English, Polish	...
Country of origin	...	China	...
Manufacturer / Brand	ETI	BCS	SATEL
Guarantee	2 years	3 years	2 years