





	WEATHER STATION UT-A12T UNI-T	POWER METER WITH LCD DISPLAY UT-230B-EU UNI-T	REMOTE CONTROL FOR LED LIGHTING CONTROLLERS LED-CONTROL-W/RF 2.4 GHz, MONO, CCT MiBOXER / Mi-Light	STYROFOAM PLUG SM-95/EPN*P4 Elektro-Plast
				
	14.24 EUR 14.24 EUR	27.17 EUR 27.17 EUR	7.69 EUR 7.69 EUR	2.04 EUR 2.04 EUR
Device type	...	Power meter with LCD display
Measurement	Temperature / relative humidity
Power measurement	...	0.1 ... 3680 W
In package	4 pcs The price for package
Application	Works with LED lighting : single-color (MONO) 12-24V LED strips, white LED strips with adjustable color temperature (CCT) 12-24V	...
AC voltage measurement	...	100 ... 260 V
Measurement range	-10 °C ... 50 °C ± 1 °C
Length	95.5 mm
Number of channels	4	...
Maximal current	...	16 A
Wireless	2.4 GHz	...
Maximal load	...	3680 W
Radio communication range (at open area)	30 m	...
Measurement of humidity	20 % ... 95 % ± 5 %
Diameter	Ø 20 mm / Ø 24 mm
Range of displayed power	...	0.0 ... 9999 W
Thickness of the Styrofoam	≥ 100 mm
Range of displayed voltage	...	0.0 ... 9999 V
Diameter of the screw	Ø 4 mm ... Ø 5 mm
Range of displayed cumulative electricity	...	0.000 ... 9999 kWh
Cumulative cost of electricity	...	0.00 ... \$ 9999
Color	White	...	White	...
Operation temp	-10 °C ... 50 °C	...	-20 °C ... 60 °C	...
Permissible relative humidity	max. 90 % (non-condensing)

Main features	<ul style="list-style-type: none"> • LCD display • Digital sensor • External temperature measuring probe : Length of the cable 2 m • Alarm function • Selectable measurement unit: °C / °F • Wall mounting • Integrated stand 	<ul style="list-style-type: none"> • Operation modes : Power consumption, Voltage, Cumulated amount of electricity, Cumulative cost of electricity, Cost of electricity (\$/kWh) • Large, readable LCD display • Simple configuration of the cost calculation setting 	Large, readable buttons	...
Housing	...	Plastic	Plastic	...
Security class	...	IP20
Socket type	...	F type (Schuko)
Power supply	1 x battery LR3 (AAA) (included)	230 V AC, 50 Hz + 1 x CR2032	2 x 1.5V, type AAA/LR03 battery (not included)	...
Weight	0.106 kg	0.165 kg	0.044 kg (without battery)	0.01 kg / 1 pcs
Dimensions	Ø 130 x 78 mm x 22 mm	130 x 65 x 80 mm	110 x 53 x 21 mm	...
Manufacturer / Brand	UNI-T	UNI-T	MiBOXER / Mi-Light	Elektro-Plast Nasielsk
Guarantee	2 years	2 years	2 years	2 years