

	<a href="#">SWITCHING ADAPTER DRP-012V015W-1AZ Delta Electronics</a>	<a href="#">UPS UT650EG-FR/UPS 650 VA CyberPower</a>	<a href="#">CABLE YTDY-8X0.5</a>
			
	13.08 EUR 13.08 EUR	71.44 EUR 71.44 EUR	0.29 EUR 0.29 EUR
Nominal power	...	360 W	...
Adapter type	Switching	...	...
Apparent Power	...	650 VA	...
Power voltage	85 ... 264 V AC	...	...
Input voltage	...	165 V ... 290 V AC	...
In section	...	...	<b>100 m . Price for 1m when buying a whole roll</b>
Input frequency	...	50 / 60 Hz (auto detection)	...
Output voltage adjustment	11 ... 14 V	...	...
Voltage tolerance	± 2 %	...	...
Inner conductor	...	...	8 x Ø 0.5 mm Cu Wire
Output voltage	12 V DC	230 V AC ± 10 % (Approximated Sine Wave)	...
Maximal load	1.25 A	...	...
Outer coating	...	...	PVC
Output power	15 W	...	...
Coating color	...	...	White
Output frequency	...	50 / 60 Hz ± 1 %	...
Efficiency	84 %	...	...
Transfer time	...	4 ms (typical)	...
Application	...	...	<ul style="list-style-type: none"> <li>• Alarm installation</li> <li>• Interphone installation</li> </ul>
Charging time (recover to 90% capacity)	...	6 hours	...
MTBF (Mean Time Between Faults)	1000000 hours	...	...
Vibration resistance	IEC60068-2-6, 10 ... 150 Hz max. 5 G for 90 minutes	...	...
Estimated battery operation time	...	<ul style="list-style-type: none"> <li>• 28 minutes @ 60 W,</li> <li>• 16 minutes @ 90 W</li> </ul>	...
Number of outputs	1 pcs	3 pcs	...
Protections	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overvoltage</li> <li>• Overload protection</li> </ul>	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Overvoltage</li> <li>• Overload protection</li> <li>• Overcharge protection</li> <li>• Phone/Fax/Modem and RJ11/RJ45 (Combo)/Network protection</li> </ul>	...

Operation state indication	...	<ul style="list-style-type: none"> <li>• LED diodes,</li> <li>• Sound signaling</li> </ul>	...
Main features	...	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• Compatible with power generators</li> <li>• Built-in EMI, RFI filter</li> </ul>	...
Application	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>	...
Housing type	DIN	Tower	...
Operation temp. / Relative humidity	-20 °C ... 75 °C / < 95 %	0 °C ... 40 °C / 0 ... 90 %	...
Weight	0.18 kg	3.75 kg	...
Dimensions	32 x 101 x 100 mm	84 x 174 x 280 mm	...
Manufacturer / Brand	Delta Electronics	CyberPower	...
Guarantee	5 years	2 years	2 years