



	EXPANSION PLUG KS-14/10X100 KLIMAS	IP CAMERA IPC2125SB-ADF28KMC-I0- BLACK Tri-Guard - 5 Mpx 2.8 mm UNIVIEW
		
	0.70 USD 0.70 USD	291.72 USD 291.72 USD
Standard	...	TCP/IP
Sensor	...	1/2.7 " Progressive Scan CMOS
Matrix size	...	5 Mpx
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	...
Drilling diameter	14 mm	...
Expansion plug length	80 mm	...
Screw dimensions	Ø 10 x 100 mm, SW-17	...
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick • Natural stone 	...
Resolution	...	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	...	2.8 mm
View angle	...	<ul style="list-style-type: none"> • 113 ° (manufacturer data) • 104 ° (our tests result)
Range of IR illumination	...	30 m
White light LED illuminator range	...	30 m
S/N ratio	...	> 56 dB
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Speaker built-in • Audio detection • Bi-directional audio streaming support
Main stream frame rate	...	25 fps @ 5 Mpx
Network interface	...	10/100 Base-T (RJ-45)

Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSH
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • Active deterrence function - Light and sound alarm • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Active deterrence function - Intelligent alarm linked to turning on white light and loudspeaker • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Privacy zones - max. 4 • Motion detection with human/vehicle silhouette recognition • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, face detection, people counting, crowd gathering estimation
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 960 mA
Power consumption	...	≤ 11.5 W
Housing	...	Compact, Metal + Plastic
Color	...	Black
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	...	0.42 kg
Dimensions	...	191 75 x 74 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	KLIMAS	UNIVIEW
Guarantee	2 years	3 years