






	<a href="#">CABLE USB3.0-WG/3.0M 3 m UNITEK</a>	<a href="#">ADAPTER USB-W/C/HDMI- W/2M 2.0 m</a>	<a href="#">IP CAMERA DS-2CD2T26G2-2I(2.8MM)(D) ACUSENSE - 1080p Hikvision</a>	<a href="#">PROXIMITY READER DS- K1F100-D8E Hikvision</a>
				
	6.27 CAD 6.27 CAD	8.73 CAD 8.73 CAD	392.36 CAD 392.36 CAD	143.51 CAD 143.51 CAD
Standard	...	...	TCP/IP	...
Cards support	...	...	...	13.56 MHz S50, Unique EM 125kHz
Sensor	...	...	1/2.8 " Progressive Scan CMOS	...
Reading distance of prox- keys	...	...	...	max. 5 cm
Matrix size	...	...	2.1 Mpx	...
Autonomous operation	...	...	...	—
Cable	USB-A plug / USB-A socket	USB-C plug - Input / HDMI plug - Output	...	...
Material	...	PVC	...	...
Keyboard built-in	...	...	...	—
Doorbell button	...	...	...	—
Length of the cable	3 m	2.0 m	...	...
Communication	...	...	...	USB 2.0
Tamper output	...	...	...	—
Resolution	...	...	1920 x 1080 - 1080p , 1280 x 720 - 720p	...
USB standard	3.0	3.1 - MHL support	...	...
Lens	...	...	2.8 mm	...
Maximal current consumption	...	...	...	200 mA
View angle	...	...	• 107 ° (manufacturer data) • 102 ° (our tests result)	...
Main features	<ul style="list-style-type: none"> <li>• High noise immunity</li> <li>• 100% copper conductor</li> <li>• Solid workmanship</li> <li>• Very flexible</li> </ul>	<ul style="list-style-type: none"> <li>• 4K resolution support,</li> <li>• Digital Audio - 8 Channels</li> <li>• Plug &amp; Play</li> </ul>	...	SAM card slot : 2 pcs
Operation temp	...	...	...	-20 °C ... 65 °C
Cable diameter	...	~ 4 mm	...	...
Permissible relative humidity	...	...	...	10 ... 90 % (non- condensing)
Compression	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Range of IR illumination	...	...	60 m	...
Alarm inputs / outputs	...	...	—	...
Audio	...	...	—	...
Memory card slot	...	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Main stream frame rate	...	...	25 fps @ 1080p	...
Network interface	...	...	10/100 Base-T (RJ-45)	...
Network protocols	...	...	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, UDP, Bonjour, SSL / TLS, PPPoE, SNMP, WebSocket, WebSockets	...
WEB Server	...	...	Built-in	...
Max. number of on-line users	...	...	6	...
ONVIF	...	...	✓	...
Mobile phones support	...	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>	...
Default admin user / password	...	...	admin / -	...
Default IP address	...	...	192.168.1.64	...
Web browser access ports	...	...	80	...
PC client access ports	...	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	...	...	8000	...
Port ONVIF	...	...	80	...
RTSP URL	...	...	<ul style="list-style-type: none"> <li>• Main stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>- with authorization</li> <li>• Sub stream :</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> <li>- with authorization</li> </ul>	...
RS-485 interface	...	...	—	...
Main features	...	...	<ul style="list-style-type: none"> <li>• Camera from AcuSense series</li> <li>• The "Darkfighter" series cameras provide a clear color image even at very poor lighting</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Configurable Privacy Zones</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Sharpness - sharper image outlines</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, scene changing, face detection, advanced face capture features</li> </ul>	...
Power supply	...	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 630 mA</li> </ul>	5 V DC from USB port
Power consumption	...	...	<ul style="list-style-type: none"> <li>• ≤ 9 W @ PoE (802.3af)</li> <li>• ≤ 7.6 W @ 12 V DC</li> </ul>	...
Housing	...	...	Compact, Metal	Plastic
Color	...	Black + Gray	White	Black
"Index of Protection"	...	...	IP67	...
Operation temp	...	...	-30 °C ... 60 °C	...
Supported languages	...	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
Weight	0.13 kg	0.06 kg	1.12 kg	0.086 kg
Dimensions	...	...	289 x 93 x 91 mm	117 x 68 x 13 mm
Manufacturer / Brand	UNITEK	...	Hikvision	Hikvision
SAP Code	...	...	311319777	302901362
Guarantee	2 years	2 years	3 years	3 years


 DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00