

| | ACCESS POINT 4G LTE +ROUTER ARCHER-MR200 2.4 GHz, 5 GHz 433 Mbps + 300 Mbps TP-LINK | WIRELESS KEYBOARD AND OPTICAL MOUSE SET Nzb-1989 | ROUTER VPN TL-ER605 TP-LINK |
|-----------------------------|--|---|---|
| |  |  |  |
| | 86.09 EUR 86.09 EUR | 13.11 EUR 13.11 EUR | 66.02 EUR 66.02 EUR |
| External connector | ... | USB 2.0 | ... |
| Frequency range | 2.4 GHz , 5 GHz | ... | ... |
| Resolution | ... | 800 / 1200 / 1600 dpi | ... |
| ... | ... | QWERTY | ... |
| Frequency band | ... | 2.4 GHz | ... |
| Antenna type | 3 x WiFi - built-in , 2 x 4G LTE | ... | ... |
| Supported operating systems | ... | Windows 7/8/10/11, Linux, Android | ... |
| Standards | IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3/3u | ... | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q |
| WAN interface | ... | ... | <ul style="list-style-type: none"> • 2 x LAN/WAN 10/100/1000 Mbps (RJ-45) • 1 x WAN x 10/100/1000 Mbps (RJ-45) • 1 x USB WAN - 3G/4G |
| LED indicators | ... | ... | Power, System, WAN, LAN, USB |
| Baud rates | <ul style="list-style-type: none"> • 5 GHz : 433 Mbps (max) + • 2.4 GHz : 300 Mbps (max) • LTE : 150 Mbps | ... | ... |
| DDNS | ... | ... | <ul style="list-style-type: none"> • DynDNS • No-IP • Peanuthull • Comexe |
| DHCP server | ... | ... | ✓ |
| Port USB | ... | ... | USB 2.0 |
| Firmware update | ... | ... | ✓ |
| Modulation type | DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM | ... | ... |
| LAN ports | <ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN • 3 x 10/100 Mbps - LAN | ... | <ul style="list-style-type: none"> • 2 x LAN 10/100/1000 Mbps (RJ-45) • 2 x LAN/WAN 10/100/1000 Mbps (RJ-45) |

| | | | |
|----------------------|--|-----|---|
| Protections | ... | ... | <ul style="list-style-type: none"> • SPI network firewall • VPN Passthrough • FTP/H.323/PPTP/SIP/IPsec ALG • Support DoS defence • Support Ping of Death defence • URL addresses filtering • Support ARP defence • IP-MAC Binding • TCP/UDP/ICMP Flood network attacks protection • TCP (Stealth FIN/Xmas/Null) scan blocking • Ping packets blocking from WAN • Access control |
| Management interface | ... | ... | <ul style="list-style-type: none"> • Omada Central Management System • Software Omada Controller • Omada Hardware Controller • Remote management • Web browser |
| Receiver sensitivity | 5 GHz : <ul style="list-style-type: none"> • 11a 54M: -74dBm • 11ac HT20: -67dBm • 11ac HT40: -64dBm • 11ac HT80: -60dBm • 11n HT20: -71dBm • 11n HT40: -70dBm 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M: -76dBm • 11n HT20: -73dBm • 11n HT40: -67dBm | ... | ... |
| LTE | ✓ | ... | ... |
| QSS | ✓ | ... | ... |
| WDS | ✓ | ... | ... |

| | | | |
|-------------------------------|--|--|--|
| Main features | <ul style="list-style-type: none"> • SIM socket • WPS/RESET button | <ul style="list-style-type: none"> • Range : 10 m • DPI adjustment • Automatic sleep mode • Plug & Play • The ergonomic shape | <ul style="list-style-type: none"> • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN, VPN Pass-through • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • MAC address cloning • DHCP client/server support • IPv6 compliance • IEEE 802.1Q VLAN • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • DMZ • IEEE 802.1x and Radius Authentication • SNMPv1/v2c/v3(MIB-2) • Reboot schedule • View topology and network status • RESET button |
| Power supply | 12 V DC / 1 A (power adapter included) | <ul style="list-style-type: none"> • Mouse : 1 x 1.5V, type AA/LR6/FR6 battery (not included) • keyboard : 1 x 1.5V, type AAA/LR03 battery (not included) | 12 V DC / 1 A (power adapter included) |
| Power consumption | ... | ... | max. 7.94 W |
| Operation temp | 0 °C ... 40 °C | ... | 0 °C ... 40 °C |
| Permissible relative humidity | 95 % (non-condensing) | ... | 10 % ... 90 % (non-condensing) |
| Weight | 0.26 kg | <ul style="list-style-type: none"> • Mouse : 0.06 kg • keyboard : 0.36 kg | 0.374 kg |
| Dimensions | 202 x 163 x 34 mm | <ul style="list-style-type: none"> • Mouse : 110 x 61 x 37 mm, • keyboard : 435 x 135 x 26 mm, • Receiver : 14 x 6 x 19 mm | 158 x 101 x 25 mm |
| Manufacturer / Brand | TP-LINK | Natec | TP-LINK |
| Guarantee | 3 years | 2 years | 5 years |