








	REAR SUPPORT FOR THE MOUNTING PROFILE USP-TN-600 FOR SOLAR PANELS	CONNECTION BOX PU-4D	ANGULAR SOCKET LE-50106 230 V 16 A LEGRAND	SINGLE-MODE ADAPTER AD-FC/FC	SINGLE-MODE ADAPTER AD-ST/ST	MULTIFUNCTION METER FOR ELECTRICAL INSTALLATIONS UT-595 UNIT	MULTI-MODE PIGTAIL WITH SC 50/125 CONNECTOR FIG-SC-MM
							
	48.40 DKK 48.40 DKK	42.33 DKK 42.33 DKK	33.54 DKK 33.54 DKK	7.48 DKK 7.48 DKK	3.30 DKK 3.30 DKK	4291.86 DKK 4291.86 DKK	6.56 DKK 6.56 DKK
Connector type	FC - simplex	ST simplex	...	SC
Material	Aluminum
Construction	single-mode	single-mode
Rated voltage	230 V / 50 Hz
Housing type	Metal	Metal
Number of intakes	...	4 - Cable glands PG-9
Maximal current load	16 A
Fiber optic type	50 / 125 µm - OM2
"Index of Protection"	...	IP67
Grounding	✓
Length	1 m
Electrical cable	max. 3 x 2.5 mm ²
Cable diameter	...	4 ... 8 mm
Cable terminals	screw terminals
Socket type	CEE 7/5
Color	Gray
Resistance measurement	<ul style="list-style-type: none"> • Test voltage 250 V : 0.05 MΩ ... 250 MΩ • Test voltage 500 V : 0.05 MΩ ... 500 MΩ • Test voltage 1000 V : 0.05 MΩ ... 1000 MΩ 	...
Measuring accuracy	0.05 MΩ ... 1000 MΩ ± (5% + 5)	...
Open circuit voltage	Test voltage ± 10 %	...
Test current	0.9 mA ... 1.1 mA	...
Short-circuit current	< 1.8 mA	...
AC voltage measurement	0 V ... 440 V ± (2% + 3) @ 1 V	...
DC voltage measurement	0 V ... ± 440 V ± (2% + 3) @ 1 V	...
Measurement of small resistances	0.01 Ω ... 200 Ω ± (2% + 5)	...
Frequency measurement	20 Hz ... 100 Hz - for reference only	...
Test of RCDs	<ul style="list-style-type: none"> • Working voltage: 220V ± 10 % • Test current: 10mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : <ul style="list-style-type: none"> - 0 ... 2000 ms ± (5% + 5) @ 1/2 x nominal value of the residual current - 0 ... 500 ms ± (5% + 5) @ 1 x nominal value of the residual current, Selective RCD - 0 ... 500 ms ± (5% + 5) @ 2 x nominal value of the residual current, Selective RCD - 0 ... 300 ms ± (5% + 5) @ 1 x nominal value of the residual current - 0 ... 300 ms ± (5% + 5) @ 2 x nominal value of the residual current - 0 ... 40 ms ± (5% + 5) @ 5 x nominal value of the residual current 	...
RCD tripping current measurement	Increasing current test: 10 mA / 30 mA / 100 mA / 300 mA / 500 mA ± 10 %	...
RCD automatic test	✓	...
Phase sequence test	100 V ... 440 V / 45 Hz ... 65 Hz	...
Continuity measurement of protective and equalizing conductors	0 Ω ... 199 Ω ± (2% + 5) Measuring current > 20 mA @ 0 ... 2 Ω	...

Line impedance measurement (L-N)	<ul style="list-style-type: none"> • 0.05 Ω ... 1.99 Ω ± (5% + 5) • 2 Ω ... 19.99 Ω ± (5% + 5) • 20 Ω ... 2000 Ω ± (5% + 5) Measuring current : 20 A / 20 ms Measuring range of prospective short-circuit current : 0 ... 26 kA	...
Short circuit loop impedance measurement (L-PE)	<ul style="list-style-type: none"> • 0.05 Ω ... 1.99 Ω ± (5% + 5) • 2 Ω ... 19.99 Ω ± (5% + 5) • 20 Ω ... 2000 Ω ± (5% + 5) Measuring current : 20 A / 20 ms Measuring range of prospective short-circuit current : 0 ... 26 kA	...
Automatic change of measuring ranges	✓	...
RS-232	—	...
USB	—	...
Main features	ceramic sleeve	ceramic sleeve	<ul style="list-style-type: none"> • Warning of using high voltage during the measurement, • Phase switch 0° / 180° during RCD test, • Automatic identification of AC/DC voltage, • Reset function for measuring low resistances, • Large, readable LCD display with backlight, • Buzzer, • Automatic power-off, • Low battery indicator, • Aesthetic and solid construction 	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	≤ 85 % (non-condensing)	...
Power supply	8 x 1.5V, type AA/LR6/FR6 battery - included	...
Weight	0.32 kg	...	0.038 kg	1.1 kg	...
Dimensions	600 x 35 x 35 mm	100 x 100 x 37 mm	Ø 43 x 84 mm	210 x 175 x 90 mm	...
Manufacturer / Brand	LEGRAND	UNI-T	...
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00