






	<a href="#">TRANSFORMER EXTENSION MODULE MRP-400A ZAMEL</a>	<a href="#">EXPANSION PLUG JPK-12X220/M5 EBOLT</a>	<a href="#">RJ45 CONNECTOR TOOL KIT NS-468/KIT</a>	<a href="#">USB SWITCH US-221A ATEN</a>	<a href="#">ACCESS CONTROL PANEL ACCO-NT2 SATEL</a>
					
	4615.38 CZK 4615.38 CZK	50.46 CZK 50.46 CZK	236.80 CZK 236.80 CZK	917.66 CZK 917.66 CZK	9587.69 CZK 9587.69 CZK
Support	MEW-01	...	...	...	...
Maximum continuous primary current	400 A	...	...	...	...
Inputs	...	...	...	...	• 8 pcs - Mainboard inputs • max. 264
Gear	3000 : 1	...	...	...	...
Frequency range	50/60 Hz	...	...	...	...
Connectors	...	...	...	• 2 x socket USB 2.0 B - Computer interface • 1 x socket USB 2.0 A - Connecting to the device	...
Wire gauge	36 mm (max)	...	...	...	...
Material	...	• Expansion plug, Polypropylene • Screw, Steel galvanized • mounting screw, Steel galvanized	...	...	...
Length of the cable	...	...	...	180 cm	...
Tested cables	...	...	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C), RJ12 (6P6C)	...	...
Drilling diameter	...	12 mm	...	...	...
USB standard	...	...	...	2.0	...
Outputs	...	...	...	...	• 8 pcs - Mainboard inputs • max. 264
Expansion plug length	...	215 mm	...	...	...
Communication	...	...	...	...	• 2 x RS-485 • Expander bus - up to 32 expander modules
Screw dimensions	...	Ø 8 x 220 mm, Internal thread M5	...	...	...
Screw	...	Ø 5 x 16 mm	...	...	...
Events memory	...	...	...	...	• Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Users + admins	...	...	...	...	• 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Application	...	for Styrofoam 150 mm	Plug RJ45 (8P8C) , Plug RJ12 (6P6C) , Plug RJ11 (6P4C) / DEC	...	...
Output load	...	...	...	...	• OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC

Main features	<ul style="list-style-type: none"> <li>• Openable core</li> <li>• TH-35 rail mounting</li> </ul>	...	...	<ul style="list-style-type: none"> <li>• LED indication</li> <li>• Support for platforms: Windows, Linux, Mac, Sun</li> <li>• Overload protection</li> <li>• USB A / USB B cable included - 1.8 m</li> </ul>	<ul style="list-style-type: none"> <li>• Support for up to 255 access control modules</li> <li>• Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition)</li> <li>• Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway)</li> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Ability to assign 4 identifiers and a keyfob to a single user,</li> <li>• Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user,</li> <li>• Up to 256 access calendars, weekly schedules, daily schedules, time frames</li> <li>• Ability to control the control panel outputs by using keyfobs</li> <li>• Implementation of logic functions on inputs and outputs</li> <li>• Support for turnstiles</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> </ul>
Power supply	...	...	Battery 9 V 6LR61 (not included)	...	12 V DC / 140 mA (max)
Battery backup support	...	...	...	...	—
Operation temp	<ul style="list-style-type: none"> <li>• -15 °C ... 60 °C - SC-36</li> <li>• -25 °C ... 50 °C - MRP-400A</li> </ul>	...	...	...	-10 °C ... 55 °C
Permissible relative humidity	...	...	...	...	93 % (non-condensing)
Weight	1.332 kg (total)	...	0.12 kg 0.77 kg (total)	0.05 kg	0.096 kg
Dimensions	<ul style="list-style-type: none"> <li>• 87 x 43 x 68 mm - SC-36 (single element)</li> <li>• 90 x 67 x 42 mm - MRP-400A</li> </ul>	...	101 x 107 x 28 mm 260 x 170 55 mm (case)	72 x 66 x 25 mm	151 x 69 x 17 mm
Manufacturer / Brand	ZAMEL	EBOLT	...	ATEN	SATEL
Guarantee	2 years	2 years	2 years	2 years	2 years