




	<a href="#">EXTENDER HDMI-EX-701R-4KV2</a>	<a href="#">SWITCH POE APTI-POE0802G-120W-V2 8-PORT</a>	<a href="#">SWITCH POE DS-3E0310HP-E 8-PORT Hikvision</a>
			
	46000.00 HUF 46000.00 HUF	25384.62 HUF 25384.62 HUF	55480.77 HUF 55480.77 HUF
LAN ports	...	10 x RJ45 ( 8 x PoE (802.3af/at) )	<ul style="list-style-type: none"> <li>• 2 x RJ45 10/100/1000 Base-TX - Uplink,</li> <li>• 8 x RJ45 10/100 Base-TX ( 1 x Hi-PoE (802.3af/at/bt) + 7 x PoE (802.3af/at) )</li> </ul>
Management	...	—	—
Maximal output power	...	30 W / port PoE	...
Supported HDMI resolutions	720p, 1080i, 1080p, 800 x 600, 1280 x 960, 1280 x 800, 1280x768, 1680x1050, 1360 x 768, 1366 x 768, 1600 x 900, 1024 x 768 3840 x 2160 - 4K UHD, max. 4096 x 2160	...	...
Maximal transmission range	<ul style="list-style-type: none"> <li>• 70 m @ UTP cat. 6 / 6A / 7 @ 4K UHD</li> <li>• 50 m @ UTP cat. 5e @ 4K UHD</li> </ul>	...	...
LED diodes	...	LAN, PoE	Power, PoE Max, PoE, Link/Act
Transmission speed	...	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 2 x Port LAN,</li> <li>• 10 / 100 Mbps : 8 x LAN &amp; PoE ports</li> </ul>	10 / 100 / 1000 Mbps : 2 LAN ports 10 / 100 Mbps : 8 LAN & PoE ports
Supported audio formats	LPCM, DTS-HD, DTS-Audio, Dolby Digital 5.1CH, Dolby Atmos	...	...
Maximal total power	...	120 W	110 W
Supported HDMI standard	2.0	...	...
MAC addresses table	...	2k	16k
HDCP	2.2	...	...

Main features	<ul style="list-style-type: none"> <li>• IR receiver / IR transmitter - External</li> <li>• Very good image quality with no visible distortions caused by compression</li> <li>• No delays in video transmission</li> <li>• Built-in HDMI signal splitter in the transmitter</li> <li>• Built-in ESD protection</li> <li>• EDID support</li> <li>• HDR10 support</li> </ul>	<ul style="list-style-type: none"> <li>• 2 x Port Uplink</li> <li>• Range PoE : 250 m - The EXTEND mode enabled</li> <li>• Mounts for mounting the device in the RACK 10" system</li> </ul>	...
Operation modes	...	...	<ul style="list-style-type: none"> <li>• Extend On : 150 m, 10 Mbps @ Hi-PoE (802.3bt) / 250 m, 10 Mbps @ PoE (802.3af/at)</li> <li>• Extend Off : 100 m, 100 Mbps @ Hi-PoE (802.3af/at/bt)</li> </ul>
Certificates	...	CE	CE
Power consumption	8 W (total)	...	...
Power supply	5 V DC / 2 A - Transmitter (power adapter included)	230 V AC	48 V DC / 2.5 A (power adapter included)
Operation temp	-20 °C ... 60 °C	-10 °C ... 55 °C	...
Permissible relative humidity	0 % ... 90 % (non-condensing)	...	...
Weight	0.14 kg	0.84 kg	0.57 kg
Manufacturer / Brand	...	APTI	Hikvision
SAP Code	...	...	301801346
Dimensions	85 x 75.5 x 16.5 mm - Transmitter or receiver dimensions	200 x 118 x 44 mm	218 x 107 x 28 mm
Guarantee	2 years	2 years	3 years