




	EXTENDER HDMI+USB-EX-100	BLANK MODULE AD-LS/ZP-45X45 System 45	SMART SWITCH WITH TEMPERATURE MEASUREMENT ATLO-TS1-TUYA Wi-Fi, Tuya Smart
			
	169.26 AUD 169.26 AUD	1.23 AUD 1.23 AUD	21.35 AUD 21.35 AUD
Application	...	System 45	<ul style="list-style-type: none"> • Temperature measurement • switching devices on/off
Material	...	Plastic	...
Supported HDMI resolutions	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Maximal transmission range	100 m UTP cat. 5e, 6
Temperature measurement	-50 °C ... 125 °C ± 0.5 °C
Max. number of receivers working in the same time	253
Manufacturer / Brand	...	STASINSKI / JAVEL	...
Protocols	HDbiT
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • The devices do not require direct connection, they also operate via the LAN network • Audio transmission via network
Maximal total load	3000 W
Total maximal current	16 A
Number of inputs	1
Number of outputs	1
Power supply	2 x 5 V DC / 1 A (power adapter included)	...	85 ... 250 V
Connector type	screw terminals
Wireless	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n • Bluetooth
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS

Main features	<ul style="list-style-type: none"> • The need for a separate power supply for the transmitter and receiver 	...	<ul style="list-style-type: none"> • Temperature Sensor : DS18B20 - Measuring accuracy $\pm 0.5 \text{ }^\circ\text{C}$ @ $-10 \text{ }^\circ\text{C}$... $85 \text{ }^\circ\text{C}$ • Warning indication about exceeding the preset temperature, • schedule, • timer, • remote access, • voice control, • Pairing button, • Wi-Fi indicator, • Temperature history graph, • Settings memory after power failure, • Energy measurement, energy consumption history graph, • For indoor use
Housing	Plastic
Color	...	White	White
Operation temp	$-10 \text{ }^\circ\text{C}$... $60 \text{ }^\circ\text{C}$...	$0 \text{ }^\circ\text{C}$... $40 \text{ }^\circ\text{C}$
Permissible relative humidity	0 % ... 90 % (non-condensing)	...	5 % ... 90 % (non-condensing)
Weight	0.168 kg	0.006 kg	0.1 kg (total)
Dimensions	110 x 89 x 26 mm - Transmitter or receiver dimensions	45 x 45 x 16 mm	<ul style="list-style-type: none"> • 93 x 55 x 30 mm • 95 cm (cable length) - Probe
Guarantee	2 years	2 years	2 years