

	POWER DISTRIBUTION UNIT ACAR-F5/FA/RACK	COUPLER GG-5.5
		
	27.34 EUR 27.34 EUR	0.59 EUR 0.59 EUR
Rated voltage	230 V AC / 50 Hz	...
Nominal load current	max. 10 A (total)	...
Maximal total load	2300 W	...
Nominal voltage of surge suppressor	250 V / 50 Hz	...
Connector type	...	Coupler Socket 2.1 : 5.5 mm / Socket 2.1 : 5.5 mm
Protection level of surge suppressor	≤ 1.3 kV (L/N)	...
Number of outlets	5 grounded outlets 10A/250V	...
Material	...	Metal / PET
Automatic delayed fuse	10 A / 250 V	...
Nominal stroke current	2 kA (L/N) - 8/20 μs	...
Maximum stroke current	10 kA (L/N) - 8/20 μs 2 type	...
Response time	< 25 ns	...
Switch	two-way, with light indication	...
Main features	<ul style="list-style-type: none"> • Current paths shutters • DC filter to eliminate interferences : ≤ 35 dB 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance
Housing	RACK 19", 1U, Plastic - non-flammable	...
Weight	0.93 kg	0.006 kg
Dimensions	484 x 54 x 55 mm	Ø 10 x 40 mm
Length of the cable	2.9 m	...
Guarantee	2 years	2 years