



	<a href="#">EXTENDER HDMI-EX-60-4K-MINI</a>	<a href="#">ACCESS CONTROLLER PR622-G ROGER</a>
		
	77.24 EUR 77.24 EUR	128.57 EUR 128.57 EUR
Cards support	...	Unique EM 125kHz
Supported HDMI standard	2.0	...
HDCP	2.2	...
Reading distance of prox-keys	...	max. 15 cm
Autonomous operation	...	✓
Doorbell button	...	—
Relay contacts load	...	1.5 A / 30 V
Battery backup support	...	—
Keyboard built-in	...	—
Input lines	...	3
Output lines	...	3
Tamper output	...	✓
Communication	...	<ul style="list-style-type: none"> <li>• RS-485</li> <li>• RACS (Roger)</li> </ul>
Average current consumption	...	50 mA
Supported HDMI resolutions	<ul style="list-style-type: none"> <li>• 480i @ 60Hz,</li> <li>• 480p @ 60Hz,</li> <li>• 576i @ 50Hz,</li> <li>• 576p @ 50Hz,</li> <li>• 720p @ 50/60Hz,</li> <li>• 1080i @ 50/60Hz,</li> <li>• 1080p @ 50/60Hz,</li> <li>• 4K UHD @ 24/25Hz</li> </ul>	...
Maximal transmission range	60 m UTP cat. 6, 6A, 7	...
Environment class	...	IV
"Index of Protection"	...	IP67
Main features	<ul style="list-style-type: none"> <li>• Possibility to power only the transmitter (in the set there is one power adapter)</li> <li>• Protections : lightning, Overvoltage, ESD</li> </ul>	<ul style="list-style-type: none"> <li>• Unique EM 125kHz proximity reader built-in</li> <li>• PRT series readers support</li> <li>• 4000 indexed users</li> <li>• History of 32000 events</li> <li>• 99 General Purpose Schedules</li> <li>• 250 access groups</li> <li>• Tamper detection - removing from mounting surface</li> </ul>

Permissible relative humidity	...	10 ... 95 % (non-condensing)
Power supply	5 V DC / 2 A	10 ... 15 V DC
Weight	...	0.15 kg
Current consumption	≤ 5 W (total)	...
Operation temp	-20 °C ... 60 °C	-25 °C ... 60 °C
Transmitter and receiver weight	0.09 kg	...
Manufacturer / Brand	...	ROGER
Dimensions	67 x 39 x 22 mm	85 x 85 x 27 mm
Guarantee	2 years	3 years