

	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-B-EA15FSR4(2.0) - 5 Mpx 2.8 mm BCS BASIC	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V2-36 2Mpx / 5Mpx 3.6 mm
	29.97 CHF 29.97 CHF	27.66 CHF 27.66 CHF
Standard	AHD / HD-CVI / HD-TVI / CVBS	AHD, HD-CVI, HD-TVI
Matrix size	...	5 Mpx
Resolution	<ul style="list-style-type: none"> • 2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps • 2880 x 1620 - 5 Mpx @ AHD @ 20 fps • 2880 x 1620 - 5 Mpx @ HD-TVI @ 20 fps / 12.5 fps • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps / 25 fps • 1920 x 1080 - 2 Mpx @ AHD / HD-CVI / HD-TVI @ 30 fps / 25 fps • 960 x 576 - 960H @ PAL / NTSC 	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Sensor	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Lens	2.8 mm	3.6 mm
Range of IR illumination	40 m	20 m
IR illuminator power adjustment	Automatic	Automatic
View angle	• 109 °	• 77 ° (manufacturer data) • 70 ° (our tests result)
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch
OSD menu	OSD menu available via recorder	✓

Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC - configurable Back Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Mirror - Mirror image 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only
Housing	Dome, Metal	Dome - Metal
Color	White	Graphite
Vandal-proof	...	—
Mechanical protection class	—	...
"Index of Protection"	IP67	IP67
Power supply	12 V DC / 283 mA	12 V DC / 230 mA
Power consumption	< 3.4 W	≤ 2.8 W
Operation temp	-20 °C ... 60 °C	-20 °C ... 60 °C
Weight	0.33 kg	0.42 kg
Dimensions	Ø 111 x 98 mm	Ø 96 x 91 mm
Supported languages	...	Polish, English
Manufacturer / Brand	BCS BASIC	APTI
Guarantee	3 years	2 years