



	POWER SUPPLY ADAPTER PFM300 DAHUA	IP CAMERA IPC-HFW3549T1-ZAS-PV-27135 TiOC Full-Color - 5 Mpx 2.8 ... 13.5 mm - MOTOZOOM DAHUA
		
	15.77 EUR 15.77 EUR	582.93 EUR 582.93 EUR
Adapter type	Switching	...
Standard	...	TCP/IP
Power voltage	230 V AC	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Output voltage	12 V DC	...
Matrix size	...	5 Mpx
Maximal load	2 A	...
Output power	24 W	...
Number of outputs	1 pcs	...
Power connectors type	2.1/5.5 mm Straight plug	...
Housing type	Plastic	...
Main features	Splash-proof casing	...
Operation temp	-30 °C ... 70 °C	...
Resolution	...	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	...	2.8 ... 13.5 mm - Motozoom
View angle	...	113 ° ... 36 ° (manufacturer data)
Range of IR illumination	...	40 m
White light LED illuminator range	...	50 m
Min. illumination	...	0.003 Lux / F1.0 (color)
S/N ratio	...	> 56 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	AI H.265 / H.265+ / AI H.264 / H.264+
Alarm inputs / outputs	...	1 / 1
Audio	...	<ul style="list-style-type: none"> • Microphone built-in - 2 pcs, • External microphone input, • Speaker built-in • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	20 fps @ 5 Mpx 25 fps @ 4 Mpx

Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP
WEB Server	...	Built-in
Max. number of on-line users	...	20
ONVIF	...	21.12
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80
RTSP URL	...	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	...	<ul style="list-style-type: none"> • Active deterrence function, Alternately flashing LEDs: red and blue - frequency configuration, Siren sound - 3 volume levels • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Quick Pick - AI technology enabling, together with the recorder, quick identification of interesting objects (people/vehicles) based on an artificial intelligence algorithm. It allows to extract and compare the colors of clothes and vehicles • SMD 4.0 - searching for an object classified as: human, motor vehicle - increased detection distance and resistance to false alarms • AI SSA AI Smart Scene Adaptive - scene auto-adaptation using deep learning algorithms to detect environmental conditions such as rain, fog, backlight, low light and flickering, in order to set the optimal image parameters • BLC/HLC - Back Light / High Light Compensation • Day/night mode • Full Color - colorful night mode • Auto White Balance • AGC - Automatic Gain Control • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Mirror - Mirror image • Light and sound alarm • White light (LED) illuminator built-in : 2 LEDs • IVS analysis : crossing the line (tripwire), intrusion - classification of people and vehicles, scene changing, video tampering, Audio detection

Power supply	...	<ul style="list-style-type: none"> PoE (802.3af), 12 V DC / 570 mA
Power consumption	...	max. 8.2 W @ PoE max. 6.8 W @ 12 V
Housing	...	Compact - Metal
Color	...	White + Black
"Index of Protection"	IP23	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.16 kg	1.05 kg
Dimensions	140 x 89 x 37 mm	289 x 95 x 85 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Ukrainian, Hungarian, Italian
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years

