




	<a href="#">MULTIPURPOSE WIRED DETECTOR XD-2-BR SATEL</a>	<a href="#">POWER DISTRIBUTION UNIT OR-AE-13144 (4 OUTLETS + 2 USB) ORNO</a>
		
	282.58 NOK 282.58 NOK	199.40 NOK 199.40 NOK
Support	Alarm control panel	...
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	10 A
Maximal total load	...	2300 W
Detection	Opening the door or window, Vibrations, Water	...
Environmental class EN 50130-5	II	...
Protection class (Grade)	2	...
Number of outlets	...	<ul style="list-style-type: none"> <li>• 4 grounded outlets 10A/250V,</li> <li>• 2 USB ports 2.1A/5V</li> </ul>
Sensitivity adjustment	—	...
Switch	...	—
Length of the cable	...	1.4 m
Alarm signaling	LED indicator, Signal to control panel	...
Housing	...	Plastic
Relay contacts rating (resistive load)	40 mA / 24 V DC	...
Power supply	12 V DC / 14 mA (max)	...

Main features	<ul style="list-style-type: none"> <li>• Operation modes : <ul style="list-style-type: none"> <li>- Magnetic detector</li> <li>- Opening the door or window</li> <li>- input for connecting a NC type wired detector</li> <li>- 1 Alarm output <ul style="list-style-type: none"> <li>- Shock detector</li> </ul> </li> <li>- Detection of shocks and vibrations associated with attempts to force a door or window</li> <li>- Range : 3 m</li> <li>- input for connecting a NC type wired detector</li> <li>- 1 Alarm output <ul style="list-style-type: none"> <li>- Shock and magnetic detector</li> </ul> </li> <li>- Detection of shocks and vibrations associated with attempts to force a door or window</li> <li>- Opening the door or window</li> <li>- input for connecting a NC type wired detector</li> <li>- 2 Alarm outputs <ul style="list-style-type: none"> <li>- Water flood detector -</li> </ul> </li> </ul> </li> <li>The required FPX-1 probe is available separately</li> <li>- detecting the presence of water in spaces where there is a risk of leakage</li> <li>- 1 Alarm output</li> <li>• Tamper detection - opening the enclosure, removing from mounting surface</li> <li>• LED indication</li> <li>• Supply voltage control</li> <li>• 2 magnets included (for surface and flush mounting)</li> <li>• Compliance with EN 50130-4, EN 50130-5, EN 50131-1, EN 50131-2-6 standards</li> </ul>	...
Color	Brown	White + Gray
Operation temp	-10 °C ... 55 °C	...
Weight	0.023 kg	0.35 kg
Dimensions	<ul style="list-style-type: none"> <li>• 20 x 102 x 23 mm (detector)</li> <li>• Ø 10 x 28 mm ( magnet )</li> </ul>	94 x 78 x 78 mm
Manufacturer / Brand	SATEL	ORNO

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	2 years	2 years
-----------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00