




| | SMART GARAGE DOOR CONTROLLER ATLO-GDC2-TUYA Wi-Fi, Tuya Smart | SMART LIGHT SWITCH ATLO-WB1-TUYA Wi-Fi, Tuya Smart | CONNECTOR FOR LED STRIPS AD-TL-6499/Z/T/RGB 10 mm ORNO |
|-----------------------|--|--|---|
| |  |  |  |
| | 14.85 EUR 14.85 EUR | 11.74 EUR 11.74 EUR | 0.98 EUR 0.98 EUR |
| Application | garage doors | Works with lighting - switching on/off | Works with LED lighting RGB |
| Strip width | ... | ... | 10 mm |
| Power supply | 100 ... 240 V AC, 50 / 60 Hz | ... | ... |
| Number of inputs | 1 x Reed switch | ... | ... |
| Rated voltage | ... | 100 ... 240 V AC, 50 / 60 Hz | ... |
| "Index of Protection" | ... | ... | — |
| Maximal power voltage | ... | ... | 48 V |
| Maximum power | ... | 300 W (for each output) | ... |
| Break distance | 3 ... 15 mm | ... | ... |
| Rated current | ... | max. 10 A | ... |
| Number of buttons | ... | 1 | ... |
| Number of outputs | 1 x NO | 1 | ... |
| Manufacturer / Brand | ... | ... | ORNO |
| Connector type | ... | screw terminals | ... |
| Wireless | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n | Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n | ... |
| Mobile phones support | <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS | <ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS | ... |
| Main features | <ul style="list-style-type: none"> • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • Magnetic contact included • Garage door open alarm • Opening and closing history • STATUS indicator • ON/OFF button • For indoor use | <ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication | ... |
| Housing | ... | Plastic | ... |
| Color | ... | White | White |
| Operation temp | 0 °C ... 40 °C | -20 °C ... 50 °C | ... |

| | | | |
|-------------------------------|--|-----------------|------------|
| Permissible relative humidity | ... | ≤ 80 % | ... |
| Weight | 0.16 kg | 0.09 kg | 0.002 kg |
| Dimensions | <ul style="list-style-type: none"> • 90 x 39 x 25 mm • 5 m (cable length) - Reed switch • 1 m (cable length) - Power supply | 87 x 86 x 41 mm | 30 x 20 mm |
| Guarantee | 2 years | 2 years | 2 years |

