






	SMART GARAGE DOOR CONTROLLER ATLO-GDC1-TUYA Wi-Fi, Tuya Smart	EXPANSION PLUG KS-10/6X120 KLIMAS	EXPANSION PLUG KW-10/5X80 KLIMAS	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-TA48VWR6-G - 8.3 Mpx 2.7 ... 13.5 mm - MOTOZOOM	BATTERY 12V/17AH- EUROPOWER-EP
					
	6020.19 HUF 6020.19 HUF	117.31 HUF 117.31 HUF	54.81 HUF 54.81 HUF	54711.54 HUF 54711.54 HUF	31413.46 HUF 31413.46 HUF
Battery capacity	17 Ah
Rated voltage	12 V
Battery charging current	max. 5.1 A
Standard	AHD, HD-CVI, HD-TVI, CVBS	...
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery
Material	...	• Expansion plug, Polypropylene • Screw, Steel galvanized	• Expansion plug, Polypropylene • Screw, Steel galvanized
Sensor	1/2.7 " Progressive Scan CMOS	...
Number of inputs	1 x Reed switch
Drilling diameter	...	10 mm	10 mm
Matrix size	8.3 Mpx	...
Number of outputs	1 x Motor
Connector	B1 / M5 screw
Expansion plug length	...	60 mm	50 mm
Break distance	3 ... 15 mm
Battery lifetime	6 ... 9 years
Screw dimensions	...	Ø 6 x 120 mm, SW-10	Ø 5 x 80 mm, PZ-2
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Application	garage doors	• Concrete • Solid clay brick • Solid sand-lime brick	• Concrete • Solid clay brick • Solid sand-lime brick
Mobile phones support	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD @ 15 fps , 2592 x 1944 - 5 Mpx @ 20 fps , 2560 x 1440 - 4 Mpx @ 25 fps , 960 x 576 - 960H, PAL	...
Lens	2.7 ... 13.5 mm - Motozoom, AutoFocus	...
Main features	• schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • Magnetic contact included • Garage door open alarm • Opening and closing history • STATUS indicator • ON/OFF button • For indoor use
Operation temp	0 °C ... 40 °C

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

View angle	<ul style="list-style-type: none"> • 105 ° ... 33 ° (manufacturer data) • 101 ° ... 33 ° @ HD-CVI (our tests result) 	...
Range of IR illumination	60 m	...
IR illuminator power adjustment	Automatic	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	<ul style="list-style-type: none"> • Microphone built-in - HD-CVI only 	...
OSD menu	✓	...
Main features	<ul style="list-style-type: none"> • Motozoom lens - AutoFocus • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones • Sharpness - sharper image outlines 	...
Power supply	5 V DC / 2 A micro USB socket (power adapter not included)	12 V DC / 920 mA	...
Power consumption	≤ 11 W	...
Housing	Compact, Metal	...
Color	Dark graphite	...
"Index of Protection"	IP66	...
Operation temp	-20 °C ... 60 °C	...
Weight	0.03 kg	0.58 kg	6.1 kg
Dimensions	<ul style="list-style-type: none"> • 60 x 44 x 23 mm • 5 m (cable length) - Reed switch 	210 x 90 x 90 mm	181 x 77 x 167 mm
Manufacturer / Brand	...	KLIMAS	KLIMAS	BCS	...
Guarantee	2 years	2 years	2 years	3 years	2 years