




	SWITCH POE RG-S2915-24GT4MS-P-L 24-PORT RUIJIE	BATTERY 12.8V/25AH/LIFEPO4-EP EUROPOWER	FLUSH BOX INSTALL-BOX/95X95/EPN Elektro-Plast	SWITCH POE APTI-POE0402-60W 4-PORT	MULTI-SOCKET PLUG WITH SWITCH MCE-31 3680 W MACLEAN ENERGY
					
	6615.33 DKK 6615.33 DKK	1760.97 DKK 1760.97 DKK	23.01 DKK 23.01 DKK	275.41 DKK 275.41 DKK	26.78 DKK 26.78 DKK
Battery capacity	...	25 Ah
Number of sections	1
Rated voltage	...	12.8 V	230 V / 50 Hz
"Index of Protection"	...	---
Battery charging current	...	max. 12 A
Maximal total load	3680 W
Battery type	...	LiFePO ₄ , lithium-iron-phosphate battery
Total maximal current	16 A
Number of outlets	2 pcs 2P+Z
Battery lifetime	...	> 2000 cycles @ 80 % DoD
Grounding	✓
Connector	...	M5 screw
LED diodes	LAN, WAN, PoE	...
Material	Plastic
Color	Brick red + White	...	White
LAN ports	<ul style="list-style-type: none"> • 24 x RJ45 10/100/1000 Base-T (24 x PoE (802.3af/at)), • 4 x port SFP - Uplink • 1 x RJ45 - Configuration possibility from PC, • 1 x USB - Configuration possibility from PC 	6 x RJ45 (4 x IEEE 802.3af)	...
Maximal output power	15.4 W / port PoE	...
Management	✓	---	...
Number of fan coolers	2
Transmission speed	<ul style="list-style-type: none"> • 10/100/1000 Mbps : 24 LAN & PoE ports Uplink ports • 100/1000/2500 Mbps - 4 x SFP ports 	<ul style="list-style-type: none"> • 10 / 100 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 4 x LAN & PoE ports 	...
Maximal total power	370 W	60 W	...
Switching capacity	68 Gb/s
Forwarding rate	51 Mpps
MAC addresses table	16k	2k	...
Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee

Main features	<ul style="list-style-type: none"> • Can be mounted in a Rack cabinet • Switch is managed through the web and the cloud (Ruijie Reye application) • Access Control List - ACL package filtering based on source and destination IP addresses • IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs • DHCP client • BPDU Filtering/Guard • Loop back detection • Spanning Tree STP/RSTP • Errdisable Recovery • IGMP Snooping V1/V2/V3 • DHCP snooping support • Port mirroring function • Loop Protection • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200.000 h 	...	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • Cover mounting with screws • 4 Mounting screws, 4 special screws with holders to fastening to the wall - included 	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 200 m - The EXTEND mode enabled 	Switch built-in - with light indication
Certificates	CE, RoHS	CE	...
Protections	Protection against lightning discharges : 10 kV
Housing	Desktop, Metal	Plastic
Power supply	100 V ... 240 AC	230 V AC	...
Power consumption	≤ 403 W
Operation temp	0 °C ... 45 °C	0 °C ... 55 °C	...
Weight	3.04 kg	2.9 kg	0.070 kg	0.65 kg	0.1 kg
Dimensions	442 x 222 x 44 mm	181 x 76 x 166 mm	95 x 95 x 50 mm - Internal dimensions 108 x 108 x 52 mm - External dimensions	220 x 141 x 41 mm	90 x 67 x 74 mm
Manufacturer / Brand	RUIJIE	EUROPOWER	Elektro-Plast	APTI	MACLEAN ENERGY
Guarantee	3 years	5 years	2 years	2 years	2 years