



	<a href="#">AHD, HD-CVI, HD-TVI, CVBS CAMERA HAC-HFW1239TLM-A-LED-0360B-S2 Full-Color - 1080p 3.6 mm DAHUA</a>	<a href="#">IP CAMERA IPC-HDW1239V-A-IL Smart Dual Light - 1080p 2.8 mm DAHUA</a>
		
	88.37 EUR 88.37 EUR	125.83 EUR 125.83 EUR
Standard	AHD, HD-CVI, HD-TVI, CVBS	TCP/IP
Sensor	1/2.8 " CMOS	1/2.9 " Progressive Scan CMOS
Matrix size	2.1 Mpx	2.1 Mpx
Resolution	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	3.6 mm	2.8 mm
View angle	<ul style="list-style-type: none"> <li>• 86 ° (manufacturer data)</li> <li>• 82 ° (our tests result)</li> </ul>	104 °
White light LED illuminator range	40 m	30 m
Range of IR illumination	...	30 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Main stream frame rate	...	25 fps @ 1080p
Memory card slot	...	—
Alarm inputs / outputs	...	—
OSD menu	OSD menu available via DAHUA recorder	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio support via coaxial cable - HD-CVI only</li> </ul>	<ul style="list-style-type: none"> <li>• Microphone built-in</li> <li>• Audio transmission via network</li> <li>• Compliance with the AAC standard</li> <li>• Audio detection</li> </ul>
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓
Mobile phones support	...	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">DMSS</a></li> </ul>
Default IP address	...	192.168.1.108
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 37777
PC client access ports	...	37777
Mobile client access ports	...	37777
Port ONVIF	...	80

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RTSP URL	...	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> <li>• Possibility to turn off the LED illuminator</li> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• Privacy zones - max. 8</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• When Smart Dual Light is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Image rotation and mirror</li> <li>• Motion Detection - max. 4 configurable zones</li> <li>• Privacy zones - max. 4</li> <li>• Intelligent image analysis : Human detection</li> </ul>
Housing	Dome, Metal + Plastic	Dome - Metal + Plastic
Color	White + Black	White
"Index of Protection"	IP67	IP67
Vandal-proof	—	—
Power supply	12 V DC / 350 mA	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 380 mA</li> </ul>
Power consumption	≤ 4.2 W	<ul style="list-style-type: none"> <li>• ≤ 5.6 W @ PoE</li> <li>• ≤ 4.5 W @ 12 V DC</li> </ul>
Operation temp	-40 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.29 kg	0.33 kg
Dimensions	198 x 80 x 76 mm	Ø 110 x 101 mm
Supported languages	...	English, Spanish, Russian
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years

