







	MONITORS DESK MOUNT MC-691 MACLEAN	EXPANSION PLUG KW-10/6X100 KLIMAS	ACCESS POINT +ROUTER MAX18 Wi-Fi 6, 2.4 GHz, 5 GHz 574 Mbps + 1201 Mbps DAHUA	HDD MOBILE RACK ATE- HDD-TRAY AUTONE	POWER DISTRIBUTION UNIT OR-AE-13144 (4 OUTLETS + 2 USB) ORNO	STRAIGHT PLUG LE-50100 230 V 16 A LEGRAND
						
	61.05 EUR 61.05 EUR	0.25 EUR 0.25 EUR	69.86 EUR 69.86 EUR	19.40 EUR 19.40 EUR	17.63 EUR 17.63 EUR	2.50 EUR 2.50 EUR
Support	AUTONE mobile recorders
Frequency range	2.4 GHz, 5 GHz
Mounting standard	VESA 75, VESA 100
Rated voltage	230 V AC / 50 Hz	230 V / 50 Hz
Supported hard drives	1 x 2.5 "
Maximal current load	16 A
Total maximal current	10 A	...
Screen size range	13 " ... 27 "
Grounding	✓
Maximal total load	2300 W	...
Material	...	• Expansion plug, Polypropylene • Screw, Steel galvanized
Drilling diameter	...	10 mm
Bearing capacity	8 kg
Electrical cable	max. 3 x 1.5 mm ²
Expansion plug length	...	60 mm
Cable terminals	screw terminals
Plug type	CEE 7/6
Number of outlets	• 4 grounded outlets 10A/250V, • 2 USB ports 2.1A/5V	...
Antenna type	• 2.4 GHz : 2 x pcs Omnidirectional antenna - built-in • 5 GHz : 2 x Omnidirectional antenna - built-in
Tilt adjustment	-45 ° ... 45 °
Switch	—	...
Screw dimensions	...	Ø 6 x 100 mm, PZ-3
Horizontal rotation	180 °
Length of the cable	1.4 m	...
Rotation in the plane of the screen	360 °
Housing	Metal	Plastic	...
Mount tube diameter	Ø 35 mm
Application	...	• Concrete • Solid clay brick • Solid sand-lime brick
Color	Black	White + Gray	White
Standards	• LAN : IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, • Wi-Fi : IEEE 802.11 b/g/n/ac/ax
Baud rates	574 Mbps + 1201 Mbps
Protections	WPA2
LAN ports	3 x 10/100/1000 Mbps
Power supply	12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 12 W

Main features	<ul style="list-style-type: none"> • Support for Mesh technology, • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Port Security : Contact/Air (ESD/EMP) ± 8 kV / ± 6 kV • Easy and uniform management system for many devices - WiLynk application • Intuitive installation and configuration of many advanced functions
Operation temp	-10 °C ... 55 °C
Permissible relative humidity	5 % ... 95 %
Weight	6 kg	...	0.23 kg	0.068 kg	0.35 kg	0.028 kg
Dimensions	1330 x 550 x 83 mm	...	95 x 95 x 73 mm	113 x 91 x 15 mm	94 x 78 x 78 mm	Ø 37 x 62 mm
Manufacturer / Brand	MACLEAN	KLIMAS	DAHUA	AUTONE	ORNO	LEGRAND
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00