






	<a href="#">RFID PROXIMITY CARD ATLO-104N*P200</a>	<a href="#">BATTERY-FREE WIRELESS DOORBELL OR-DB-MT-156 AC 230V ORNO</a>	<a href="#">BLANK MODULE SANTRA/4170-19/EPN Elektro-Plast</a>	<a href="#">EXPANSION PLUG KW-8/4X40 KLIMAS</a>	<a href="#">EXTERNAL CAMERA DISTRIBUTION POINT EXPERT-POE/OTD-82GSEFP 8 PoE + 2 x SFP</a>
					
	1538.46 CZK 1538.46 CZK	545.48 CZK 545.48 CZK	48.68 CZK 48.68 CZK	1.78 CZK 1.78 CZK	8260.92 CZK 8260.92 CZK
Signaling mode	...	Optical - sound signaling	...	...	...
Number of ring-tones	...	36	...	...	...
In package	<b>200 pcs The price for package</b>	...	...	...	...
Material	...	...	...	• Expansion plug, Polypropylene • Screw, Steel galvanized	...
Standard	Unique EM 125kHz	...	...	...	...
Drilling diameter	...	...	...	8 mm	...
Compatibility	EM4100/4102	...	...	...	...
Expansion plug length	...	...	...	40 mm	...
Volume adjustment	...	60 ... 90 dB - 4-step	...	...	...
Possibility of programming the serial number (ID)	—	...	...	...	...
Operation range	...	max. 200 m in open area	...	...	...
LAN ports	...	...	...	...	• 8 x RJ45 10/100 Base-T ( 8 x PoE (802.3af/at) ), • 2 x SFP (Uplink) 1000 Base-X
Ability to write to internal memory	—	...	...	...	...
Frequency band	...	433.92 MHz	...	...	...
Management	...	...	...	...	—
Serial Number overprint	✓	...	...	...	...
Screw dimensions	...	...	...	Ø 4 x 40 mm, PZ-2	...
LED diodes	...	...	...	...	Power, Link/Act, PoE
Application	...	...	Santra product series	• Concrete • Solid clay brick • Solid sand-lime brick	...
Transmission speed	...	...	...	...	• 10 / 100 Mbps : 8 LAN & PoE ports, • 1000 Mbps : 2 SFP (Uplink) ports
Maximal output power	...	...	...	...	30 W @ PoE (802.3af/at) - 1 ... 8 ports
Maximal total power	...	...	...	...	115 W
MAC addresses table	...	...	...	...	16k
Operation modes	...	...	...	...	• E - EXTEND mode - ports 1, 2, 3, 4, 5, 6, 7, 8 support transmission up to 250 m • V - VLAN mode, 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • P - PoE Auto-check mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected
Number of line cables	...	...	...	...	2
Number of splice cassettes	...	...	...	...	1
Splice capacity	...	...	...	...	8
Connector type	...	...	...	...	SC / PC

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Number of adapters	...	...	...	...	4
Number of pigtails	...	...	...	...	4
Material	...	...	Plastic (ABS)	...	Metal
Color	...	...	Black	...	Gray
Manufacturer / Brand	ATLO	ORNO	Elektro-Plast Nasielsk	KLIMAS	...
"Index of Protection"	...	• IP44 - Doorbell button • IP20 - Wireless doorbell	...	...	IP55
Cable entries	...	...	...	...	3 pcs from the bottom Ø 39 mm
Main features	<ul style="list-style-type: none"> <li>Serial Number Format : 8H10D + WEG24A</li> <li>Range : ~ 11 cm</li> <li>The TK-4100 chip</li> </ul>	<ul style="list-style-type: none"> <li>The doorbell button is powered by an electromagnetic transducer, does not require any battery</li> <li>Learning function - The number of cooperated doorbell buttons (transmitters) can be increased as required</li> </ul>	...	...	<ul style="list-style-type: none"> <li>The door is closed with a lock</li> <li>Fan cooler built-in</li> </ul>
Maximum pole diameter	...	...	...	...	350 mm
External dimensions	...	...	...	...	280 x 260 x 210
Certificates	...	...	...	...	CE, RoHS
Protections	...	...	...	...	<ul style="list-style-type: none"> <li>Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> <li>Circuit Breaker : C10, protected lines L+N</li> <li>Lightning protection : <ul style="list-style-type: none"> <li>Maximal voltage : 385 V AC</li> <li>Nominal stroke current : 20 kA (8/20µs)</li> <li>Maximum stroke current : 40 kA (8/20µs)</li> </ul> </li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>230 V AC - Wireless doorbell,</li> <li>Electromagnetic transducer - Doorbell button</li> </ul>	...	...	100 ... 240 V AC, 50 / 60 Hz - Screw terminals
Operation temp	...	-40 °C ... 65 °C	...	...	-20 °C ... 65 °C
Weight	0.006 kg	<ul style="list-style-type: none"> <li>0.05 kg - Doorbell button</li> <li>0.07 kg - Wireless doorbell</li> </ul>	0.044 kg	...	5.65 kg
Dimensions	86 x 54 x 1 mm	<ul style="list-style-type: none"> <li>50 x 82 x 22 mm - Doorbell button</li> <li>81 x 81 x 72 mm - Wireless doorbell</li> </ul>	75 x 75 x 35 mm	...	280 x 260 x 205 mm
Guarantee	2 years	2 years	7 years	2 years	2 years