

	ACCESS POINT 4G LTE RUBINET RUT241 2 x 4 GHz 300 Mbps 2x2MIMO	WIRELESS WITH REPEATER TAG AT11A1042	MULTI-CONCEPT RUBINET RUT241 2 x 4 GHz 300 Mbps 2x2MIMO	WIRELESS WITH REPEATER TAG AT11A1042	ELECTRIC CABLE 2x1.5 RUBINET	FLAT ELECTRIC CABLE CAT5E 2x1.5	EXTENDED EXTENSION RUBINET	SET OF 17P / 2-WIRE CONVERTERS FOR LAN/FIBER TRANSMISSION ETH10-17P-SET 2 PCB S/E 4.0E	PLUGS BOX 4-GANG RUBINET 4-GANG 4-2P E-Box	RJ-45 PLUG-SHIELD RUBINET-N1100	RJ-45 PLUG-SHIELD RUBINET-V1100	AMB. HD-CV1 HD-TVL CABLE TV-PTIP FOR VIDEO WALLS 1.8 CHANNELS DMR18	IP CAMERA 4-CH RUBINET 4-CH 1080p 2.8mm IRCS	SMART LIGHTING DIMMER RUBINET 2-CH 2-CH WiFi 2x1.5VAC
Standard	151.45 EUR 151.45 EUR	2.59 EUR 1.59 EUR	143.55 EUR 143.55 EUR	2.77 EUR 2.77 EUR	0.26 EUR 0.26 EUR	0.66 EUR 0.66 EUR	39.15 EUR 39.15 EUR	89.63 EUR 89.63 EUR	4.84 EUR 4.84 EUR	0.45 EUR 0.45 EUR	0.43 EUR 0.43 EUR	423.14 EUR 423.14 EUR	60.08 EUR 60.08 EUR	41.27 EUR 41.27 EUR
Application		Simplex EM 120MHz		Simplex EM 120MHz										Lighting brightness control
Compatibility		EM41004102		EM41004102										
Sensor														
Number of sections														
Probability of programming the serial number (ID)														
Frequency range	2.4 GHz		2.4 GHz, 5 GHz											
Matrix size														2.1 Mpa
Ability to write to internal memory														
In package														
Input voltage														100 pcs The price for package
Security system														10 pcs The price for package
In sections														Progressive
Serial Number oversight														
Standard														
Application														
Control method														
Video inputs														
Maximal total load														
Material														
Inner conductor														
Total maximal current														
Rated voltage														
Connectors														
Number of inputs														
Control														
Head adjustment range		30-60 mm - 65 mm		30-60 mm - 65 mm										
Video outputs														
Resolution														
Number of outputs														
Antenna type	1 x Omnidirectional antenna W/Pi - 5 dBi (SMA connector) 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA DP connector)		2 x 2 MIMO Omnidirectional antenna - embedded 1 dBi @ 2.4 GHz 1 dBi @ 5 GHz											
Connector type														
Lens														
Outer coating														
Cooling color														
Audio inputs														
Wireless														
Standards	IEEE 802.11 b/g/n, 4G LTE, 3G, 2G		IEEE 802.11 b/g/n/a, 4G LTE, 3G, 2G											
View angle														
Audio outputs														
Range of IR illumination														
RS-485 interface														
Memory card slot														
Supported data rates														
Upload rates	1 to 100 Mbps 1 to 100 Mbps 1 to 11 Mbps LTE: 150 / 42 / 0.234 Mbps 4G / 3G / 2G		100 Mbps @ 2.4 GHz + 100 Mbps @ 5 GHz											
Image compression method														
Output power														
WAN interface														
LAN ports	1 x 10/100 Mbps - WAN 1 x 10/100 Mbps - LAN		1 x 10/100 Mbps - WAN / 4 x 10/100 Mbps - LAN											
Audio														
Main stream frame rate														
Operation temp. / Relative humidity														
Network interface														
Connectors description														
Optical power														
Transmission speed														
Transmitter power														
Software update														
LED indicators														
Transmission range														
Power supply PoE														
Network type														
Network protocols														
WEB Server														
Max. number of online users														
LED indicators														
ONVIF														
Default IP address														
Default admin user / password														
Web browser access ports														
PC client access ports														

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports																				
Port Uplink																			80	
Image records resolution																			8 MPn - HD-CVI / HD-TVI 8 MPn - 3840 x 2160 6.5 MPn - 3840 x 2160 6 MPn - 2880 x 1920 - HD-ETVI 5 MPn - 2592 x 1944 4 MPn - 2048 x 1536 4MxN - 1280 x 1440 5 MPn - 2048 x 1536 - AHD / HD-TVI only HD-only: 1280 x 1080 720p: 1280 x 720	
LTE																			• CVBS - 960H - 960 x 576	
DVR																			• IP: max. 8 MPn - 3840 x 2160	
ONVIF server																				
Certificates																				
Protections																				
Management interface																				
Mounting																				
Index of Protection																				
Operation temp																				
Recording speed adjustment																				
Operation modes																				
Main features																				
Recording modes																				
Supported hard drives																				
External storage devices backup																				
Power consumption																				
Searching and playback the records																				
Operation temp																				
Permissible relative humidity																				
Network functions																				
Mobile phones support																				
Alarm signals / outputs																				
PTZ control																				
Motion Detection																				
Main features																				
Mouse support																				
IR remote controller in the set																				
DVR																				
Power supply																				
Color																				
Weight																				

Dimensions	83 x 80 x 25 mm	145 x 35 x 5 mm	142 x 141 x 32 mm	245 x 35 x 5 mm	-	-	91 x 77 x 26 mm	91 x 51 x 24 mm (single element)	6 x 49 60 x 47 mm - internal dimensions 242 x 72 x 48 mm - external dimensions	-	-	260 x 238 x 48 mm	142 x 62 x 65 mm	41 x 39 x 24 mm
Supported languages	-	-	-	-	-	-	-	-	-	-	-	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian	Polish, English	-
Manufacturer / Brand	Politechnika	ATELO	BRQ/THI	ATELO	-	-	PULSAR	NYTE	Elektron-Plus	-	-	DAHTA	BOS BASIC	Stalbus
Warranty	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00