



	ACCESS CONTROL PANEL ACCO-NT SATEL	BATTERY-FREE WIRELESS DOORBELL BUTTON ATLO-DB-2/TX
		
	377.94 EUR 377.94 EUR	4.06 EUR 4.06 EUR
Support	...	ATLO-DB-2/RX
Signaling mode	...	LED indication
Operation range	...	max. 150 m in open area
Inputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264 	...
Frequency band	...	433 MHz
"Index of Protection"	...	IP44
Outputs	<ul style="list-style-type: none"> • 8 pcs - Mainboard inputs • max. 264 	...
Communication	<ul style="list-style-type: none"> • 2 x RS-485 • Expander bus - up to 32 expander modules 	...
Events memory	<ul style="list-style-type: none"> • Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module 	...
Users + admins	<ul style="list-style-type: none"> • 8000 + 1 • Max. 65 000 users in the whole ACCO NET system 	...
Output load	<ul style="list-style-type: none"> • OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC 	...

Main features	<ul style="list-style-type: none"> • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses 	...
Power supply	12 V DC / 125 mA (max)	Electromagnetic transducer
Battery backup support	—	...
Operation temp	-10 °C ... 55 °C	...
Permissible relative humidity	93 % (non-condensing)	...
Dimensions	151 x 69 x 17 mm	75 x 40 x 20 mm
Weight	0.092 kg	0.04 kg - Doorbell button
Manufacturer / Brand	SATEL	...
Guarantee	2 years	2 years