




	SURFACE BOX 2-GANG LE-776182 Valena LEGRAND	NVR APTI-N6428AI-I3 64 CHANNELS	GRAPHITE VARNISH GRAPHITE-VARNISH 2 X VIAL 1.5 ml AG TERMOPASTY
			
	11.54 CAD 11.54 CAD	605.62 CAD 605.62 CAD	4.26 CAD 4.26 CAD
Standard	...	TCP/IP	...
Number of sections	2
Supported resolutions	...	max. 12 Mpx - 4000 x 3000 px	...
Package	2 x Vial 1.5 ml (varnish + solvent)
Material	Self-extinguishing ABS
Video outputs	...	<ul style="list-style-type: none"> • 1 pcs HDMI 4K • 1 pcs HDMI • 1 pcs VGA 	...
Application	Valena product series	...	<ul style="list-style-type: none"> • Repair and renovation of graphite coatings in electronic devices, • Reconstruction of paths in printed circuit boards
Audio support	...	<ul style="list-style-type: none"> • 64 Channels - Audio from cameras, • Bi-directional audio streaming support • Compliance with the AAC standard 	...
Audio inputs	...	1 pcs CINCH	...
Audio outputs	...	1 pcs CINCH	...
Main features	<ul style="list-style-type: none"> • Density : 1.2 g/cm³ @ 20 °C, • Viscosity : 15 ... 50 Pa·s @ 20 °C • Good electrochemical corrosion protection on metal • Photosensitive varnish • Dedicated solvent (ethyl acetate) included
Image compression method	...	H.265+ / H.265 / H.264+ / H.264	...
Color	White	...	Black
Bitrate	...	640 Mbps	...
Supported hard drives	...	8 x 10 TB SATA + 1 x eSATA	...

Recording modes	...	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	...	Records backup at (.avi) format to USB (pendrive)	...
Searching and playback the records	...	Records searching: timeline or file list. Playback: forward, fast Playback max. 16 cameras in the same time @ 1080p	...
Network interface	...	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	...	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters	...
Network protocols	...	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE	...
ONVIF	...	✓	...
Default IP address	...	192.168.1.88	...
Default admin user / password	...	admin / 12345	...
Web browser access ports	...	80, 5000, 554	...
PC client access ports	...	80, 5000, 554	...
Mobile phones support	...	Access by a cloud (P2P) • Android: Free application BitVision , Android: Free application iVMS320 • Android: Free application BitVision , iOS: Free application iVMS320	...
USB	...	• 2 pcs USB 2.0 • 1 pcs USB 3.0	...
Serial ports	...	RS-485	...
Alarm inputs / outputs	...	16 / 4	...
PTZ control	...	• IP Speed Dome Cameras • RS-485 control	...
Motion Detection	...	Split the screen into zones : 22 x 18 motion zones	...
Intelligent image analysis	...	✓	...
Main features	...	• Support for intelligent image analysis, available in cameras from the APTI-AI series • D-ZOOM - Digital Zoom	...
Mouse support	...	✓	...
IR remote controller in the set	...	—	...

Switch PoE	...	—	...
Power supply	...	100 ... 240 V AC, 50 / 60 Hz	...
Power consumption	...	≤ 20 W (without HDD)	...
Operation temp	...	-10 °C ... 50 °C	...
Weight	0.10 kg	7.46 kg	...
Dimensions	160.5 x 89 x 35.5 mm	440 x 430 x 100 mm	...
Supported languages	...	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Ukrainian, Italian	...
Manufacturer / Brand	LEGRAND	APTI	AG TERMOPASTY
Guarantee	2 years	2 years	...