






	ACCESS POINT 4G LTE +ROUTER RUT956 Dual SIM 2.4 GHz 300 Mbps Teltonika	ACCESS POINT 4G LTE +ROUTER CUDY-LT400 2.4 GHz, 5 GHz, 300 Mbps	ALLEN SCREW SI-M8X35/KL-8.8	WIRED DOORBELL ATLO-DB-1	ALKALINE BATTERY BAT-LR43*P2 ENERGIZER	SWITCHING ADAPTER PS-182F FOR TERRA MS/MV/MSV MULTISWITCHES F PLUG
						
	93028.85 HUF 93028.85 HUF	25891.35 HUF 25891.35 HUF	81.73 HUF 81.73 HUF	1613.46 HUF 1613.46 HUF	403.85 HUF 403.85 HUF	9325.96 HUF 9325.96 HUF
Listen to the available sounds	
Size	M8
Adapter type	Switching
Signaling mode	Sound signaling
Material	Steel galvanized
Number of ring-tones	1
Strength class	8.8
Power voltage	100 ... 240 V AC
Volume adjustment	—
In package	2 pcs The price for package	...
Rated voltage	1.5 V	...
Output voltage	18 V DC
"Index of Protection"	IP40
Wrench size	6 mm
Maximal load	2 A
Type (size)	LR43 / 186	...
Application	TERRA Multiswitches
Output	F plug
Thread length	35 mm
Frequency range	2.4 GHz	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2100 MHz, 1800 MHz, 900 MHz, 800 MHz	50/60 Hz
Antenna type	2 x Omnidirectional antenna Wi-Fi - 3 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector) 1 x Omnidirectional antenna GPS (SMA connector)	• 2 x Omnidirectional antenna Wi-Fi • 2 x Omnidirectional antenna 4G LTE
Standards	IEEE 802.11 b/g/n, 4G, 3G, 2G, GNSS	IEEE 802.11 b/g/n
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.236 Mbps (4G / 3G / 2G)	• Wi-Fi : 300 Mbps • LTE : 150 Mbps / 50 Mbps
LAN ports	• 1 x 10/100 Mbps - WAN • 3 x 10/100 Mbps - LAN	1 x 10/100 Mbps - Uplink / LAN 3 x 10/100 Mbps - LAN
SIM socket	...	1 x mini SIM
Transmitter power	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM
DDNS	...	✓
Firmware update	...	✓
LED indicators	Power, WAN, 3 x LAN, LTE, Signal indicator	Power, INTERNET, LAN/WAN, LAN 1, LAN 2, LAN 3, WiFi, 4G
Network type	4G, 3G, 2G
LTE	✓
QSS	—
WDS	—
DHCP server	✓	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Protections	<ul style="list-style-type: none"> • WPA2-Enterprise - PEAP • WPA2-PSK • WEP • WPA-EAP • WPA-PSK • AES-CCMP • TKIP • Auto Cipher modes • Client separation • SSID hiding • MAC addresses filtering 	DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface	Web browser, Teltonika RMS application, SMS, Port RS-232, Port RS-485	Web browser
Main features	<ul style="list-style-type: none"> • Support for IoT (Internet of Things) systems, • Ability to work as a Hotspot, • Support for VoIP technology, • 2 x SIM socket, • DHCP Relay support • DHCP client list • Static / dynamic routing • VPN support • Default address : 192.168.1.1 • Configuration using the Teltonika RMS application • WAN Connection Backup thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems • Built-in GPS/GLONASS module, • Port RS-232, • Port RS-485, • Port USB 2.0, • Expanded I/O interface 	<ul style="list-style-type: none"> • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • QoS • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests 	DIN 912 compliance
Power supply	<ul style="list-style-type: none"> • 9 V DC / 1 A (power adapter included) • 9 ... 30 V DC • 9 ... 30 V DC - Passive PoE, Powering from LAN1 	12 V DC / 2.5 A (power adapter included)	...	12 V DC
Power consumption	≤ 7 W
Operation temp	-40 °C ... 75 °C	0 °C ... 45 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	5 % ... 95 % (non-condensing)
Weight	0.29 kg	0.264 kg	0.017 kg	0.06 kg	0.001 kg	0.17 kg
Dimensions	110 x 100 x 50 mm	229 x 147 x 32 mm	Ø 12.8 x 42.8 mm	62 x 88 x 24 mm	Ø 11.6 x 4.2 mm	...
Manufacturer / Brand	Teltonika	CUDY	...	ATLO	ENERGIZER	...
Guarantee	2 years	2 years	2 years	3 years	2 years	2 years