


	<a href="#">EXTENDER HDMI-EX-70IR-4KV2</a>	<a href="#">SWITCH POE APTI-POE0802G-120W-V2 8-PORT</a>	<a href="#">EXTENDER RECEIVER HDMI-EX-120/RX-V4</a>	<a href="#">WALL MOUNTING KIT USP-U30 FOR SOLAR PANELS</a>
				
	116.05 EUR 116.05 EUR	64.04 EUR 64.04 EUR	61.71 EUR 61.71 EUR	23.96 EUR 23.96 EUR
Material	...	...	...	Aluminum
Device type	...	...	Receiver	...
Tilt angle adjustment:	...	...	...	15 ° ... 50 °
LAN ports	...	10 x RJ45 ( 8 x PoE (802.3af/at) )	...	...
Management	...	—	...	...
LED diodes	...	LAN, PoE	...	...
Protocols	...	...	HDbiT	...
Transmission speed	...	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 2 x Port LAN,</li> <li>• 10 / 100 Mbps : 8 x LAN &amp; PoE ports</li> </ul>	...	...
Max. number of receivers working in the same time	...	...	237	...
Maximal output power	...	30 W / port PoE	...	...
Maximal total power	...	120 W	...	...
MAC addresses table	...	2k	...	...
Supported HDMI resolutions	720p, 1080i, 1080p, 800 x 600, 1280 x 960, 1280 x 800, 1280x768, 1680x1050, 1360 x 768, 1366 x 768, 1600 x 900, 1024 x 768 3840 x 2160 - 4K UHD, max. 4096 x 2160	...	480i, 576i, 480p, 576p, 720p, 1080i, 1080p	...
Certificates	...	CE	...	...
Maximal transmission range	<ul style="list-style-type: none"> <li>• 70 m @ UTP cat. 6 / 6A / 7 @ 4K UHD</li> <li>• 50 m @ UTP cat. 5e @ 4K UHD</li> </ul>	...	<ul style="list-style-type: none"> <li>• 100 m UTP cat. 5e</li> <li>• 120 m UTP cat. 6</li> </ul>	...
Supported audio formats	LPCM, DTS-HD, DTS-Audio, Dolby Digital 5.1CH, Dolby Atmos	...	...	...
Supported HDMI standard	2.0	...	1.3	...
HDCP	2.2	...	1.4	...
Manufacturer / Brand	...	APTI	...	...
Main features	<ul style="list-style-type: none"> <li>• IR receiver / IR transmitter - External</li> <li>• Very good image quality with no visible distortions caused by compression</li> <li>• No delays in video transmission</li> <li>• Built-in HDMI signal splitter in the transmitter</li> <li>• Built-in ESD protection</li> <li>• EDID support</li> <li>• HDR10 support</li> </ul>	<ul style="list-style-type: none"> <li>• 2 x Port Uplink</li> <li>• Range PoE : 250 m - The EXTEND mode enabled</li> <li>• Mounts for mounting the device in the RACK 10" system</li> </ul>	...	Maximum power of the mounted panel : 80 W

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Power supply	5 V DC / 2 A - Transmitter (power adapter included)	230 V AC	5 V DC / 1 A (power adapter included)	...
Power consumption	8 W (total)	...	...	...
Operation temp	-20 °C ... 60 °C	-10 °C ... 55 °C	0 °C ... 60 °C	...
Permissible relative humidity	0 % ... 90 % (non-condensing)	...	10 % ... 90 % (non-condensing)	...
Weight	0.14 kg	0.84 kg	0.13 kg	0.94 kg (total)
Dimensions	85 x 75.5 x 16.5 mm - Transmitter or receiver dimensions	200 x 118 x 44 mm	110 x 58 x 26 mm	310 x 300 x 43 mm - each item
Guarantee	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00