

	UTP / COAXIAL TRANSMITTER EOC-110KIT 2 PCS SET	SWITCH POE CS4010-8GT-110 8-PORT DAHUA	FLUSH BOX PO-80/E/PN Elektro-Plast	FLUSH BOX PK-60/K-G/E/PN Elektro-Plast	WIRELESS DOORBELL WDP-05A3 AC 230V EURA	ACCESS POINT 4G+ LTE ROUTER RUT260 2.4 GHz 300 Mbps Teltonika	WORK GLOVES WC-422S Bes-Smart WONDER GRIP	SMART ACTION TRIGGER INBOX/BLEBOX Wi-Fi CR123A	GROUNDING RESISTANCE METER UT-522 UNLT
									
	55.89 EUR 55.89 EUR	272.66 EUR 272.66 EUR	0.99 EUR 0.99 EUR	0.72 EUR 0.72 EUR	17.91 EUR 17.91 EUR	172.11 EUR 172.11 EUR	5.69 EUR 5.69 EUR	22.68 EUR 22.68 EUR	198.83 EUR 198.83 EUR
Frequency range	2.4 GHz
Number of sections	1	1
Rated voltage	3 V - Battery type CR123A	...
Transmission range	200 m @ RG6
Maximal total load
Antenna type	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Total maximal current
Number of inputs	4	...
Application	• Construction and public works. • Warehousing - packing and logistics. • DIY. • Assembly	controlling devices, triggering actions	...
Number of outputs	0	...
Standards	IEEE 802.11 b/g/n, 4G+ Cat.6 LTE, 3G
Connector type	Connection cube, screw terminals	...
Material	Plastic	Plastic
Material	Polyester + latex coating (palm coated)
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...
Montage hole diameter	Ø 68 mm
Transmission speed	10 / 100 Mbps Half Duplex	• 10 / 100 / 1000 Mbps : 8 LAN & PoE ports. • 10 / 100 / 1000 : 2 Uplink ports
Mobile phones support	• The wBox free application on Android • The wBox free application on iOS	...
Listen to the available sounds	
Signaling mode	Sound signaling
Number of ring-tones	16
Resistance measurement	40 Ω ± (2% + 20) @ 0.01 Ω 400 Ω ± (2% + 3) @ 0.1 Ω 4000 Ω ± (2% + 3) @ 1 Ω • Auxiliary resistance : 500 Ω ± 5 % • Measuring voltage : ≤ 10 V AC @ ~820 Hz
Baud rates	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 300 / 42 Mbps (4G / 3G)
Volume adjustment
Maximal output power	...	• 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports	max. 50 m in open area
Operation range
Maximal total power	...	110 W
Frequency band	433.92 MHz
Ground voltage measurement	400 V ± (1.0% + 6) @ 1 V
MAC addresses table	...	8k
Automatic change of measuring ranges
Management	...	✓
RS-232
LAN ports	1 pcs RJ45 1 pcs BNC socket	• 8 x RJ45 10/100/1000 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)) • 2 x RJ45 10/100/1000 Base-T - Uplink	• 1 x 10/100 Mbps - WAN • 1 x 10/100 Mbps - LAN
USB
Supported norms	• EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
Size	7 / S
LED diodes	...	Power, System, PoE, Link/Act
"Index of Protection"	IP44 - Doorbell button	IP20	...
Transmitter power	≤ 17.51 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA
Color	Brick red + White	Brick red	Black + Blue	Black	...
LED indicators	Power, WAN, WLAN, LAN, LTE - 3G/4G, Signal indicator

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Network type	4G, 3G
Certificates	...	CE
Housing	...	Desktop, Metal	Plastic	...
LTE	✓
QSS	---
WDS	---
DHCP server	✓
Protections	...	<ul style="list-style-type: none"> Protection against lightning discharges (common/differential) : 4 / 2 kV Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	<ul style="list-style-type: none"> WPA3-EAP WPA3-SAE WPA2-Enterprise - PEAP WPA2-PSK AES-CCMP WEP TKIP Auto Cipher modes Client separation SSID hiding MAC addresses filtering
Management interface	Web browser, Teltonika RMS application, SMS
Main features	<ul style="list-style-type: none"> Plug & Play Support for IP cameras and network devices Full transparency for networks 	<ul style="list-style-type: none"> Switch is managed through the web and the cloud (DoLink Care application) PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) Intelligent management of Power Supply Unit power's output stage protection against lightning discharges and voltage differences and strokes between devices Watchdog PoE Loop Protection Compliance with the LLDP protocol Spanning Tree STP/RSTP Port Based VLAN : 32 Data Flow Control (802.3x) DHCP client RESET button Possibility to mount to the wall 	<ul style="list-style-type: none"> Flush-mounted, for hollow walls opening lid 2 special screws with holders to fastening to the wall - included 	<ul style="list-style-type: none"> Flush-mounted, for hollow walls 2 special screws with holders to fastening to the wall - included 	The number of connected doorbells and cooperated buttons can be increased as required	<ul style="list-style-type: none"> Support for IoT (Internet of Things) systems, Ability to work as a Hotspot, Support for VoIP technology, SIM socket DHCP Relay support DHCP client list Static / dynamic routing VPN support Default address : 192.168.1.1 Configuration using the Teltonika RMS application WAN Connection Backup - (thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems) 	<ul style="list-style-type: none"> Thermal protection : 100 °C (XIXXXX) Ergonomics and comfort High grip Soft coating 	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, remote access, voice control, pWIFI technology support, Backup time : ~ 3 years 	<ul style="list-style-type: none"> Hold - stopping the meter reading, The measurement can be performed in full or simplified configuration, Warning of poor connection of leads during measurement, Large, readable LCD display with backlight, Low battery level alarm, Aesthetic and solid construction, The set includes a practical case
Power supply	...	54 V DC / 2.22 A (power adapter included)	<ul style="list-style-type: none"> 230 V AC - Wireless doorbell, Battery CR2032 3V (included) - Doorbell button 	<ul style="list-style-type: none"> 9 V DC / 1 A (power adapter included) 9 ... 30 V DC 9 ... 30 V DC - Passive PoE, Powering from LAN1 	...	6 x 1.5V, type AA/LR6/FR6 battery - included
Power consumption	...	max. 110 W	≤ 6.5 W
Operation temp	...	-10 °C ... 55 °C	-40 °C ... 75 °C	...	-20 °C ... 50 °C	5 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	≤ 80 % (non-condensing)
Weight	0.055 kg (single element)	0.52 kg	0.036 kg	0.024 kg	...	<ul style="list-style-type: none"> 0.035 kg - Doorbell button 0.09 kg - Wireless doorbell 	0.13 kg	0.027 kg	0.42 kg
Dimensions	72 x 25 x 25 mm (single element)	190 x 106 x 30 mm	<ul style="list-style-type: none"> Ø 80 x 50 mm - Internal dimensions Ø 90 x 53 mm - External dimensions 	<ul style="list-style-type: none"> Ø 60 x 47 mm - Internal dimensions Ø 67 x 48 mm - External dimensions 	<ul style="list-style-type: none"> 33 x 83 x 27 mm - Doorbell button 55 x 110 x 68 mm - Wireless doorbell 	83 x 80 x 25 mm	...	35 x 33 x 23 mm	160 x 100 x 70 mm
Manufacturer / Brand	...	DAHUA	Elektro-Plast	Elektro-Plast	EURA	Teltonika	WONDER GRIP	BleBox	UNI-T
Guarantee	2 years	3 years	2 years	2 years	2 years	2 years	...	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00