




	SMART CONTROLLER FOR ROLLER SHUTTERS SHUTTERBOX-DIN/BLEBOX Wi-Fi, 230 V AC	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1200T-IL-A-0280B-S6 - 1080p 2.8 mm DAHUA	SMART DOOR AND PEDESTRIAN DOOR CONTROLLER DOORBOX/BLEBOX Wi-Fi, 12 ... 24 V DC/AC
			
	46.47 EUR 46.47 EUR	82.98 EUR 82.98 EUR	37.91 EUR 37.91 EUR
Application	roller shutters, roof windows, awnings, drop-down screens, curtains	...	doors, pedestrian doors, lockers, drawers
Rated voltage	230 V AC	...	12 ... 24 V DC/AC
Standard	...	AHD, HD-CVI, HD-TVI, CVBS	...
Sensor	...	Progressive Scan CMOS	...
Maximal total load	2 x 1150 W (resistance load) / 2 x 150 W (inductive or capacitive load)	...	1150 W / 1150 VA
Matrix size	...	2.1 Mpx	...
Total maximal current	2 x 5 A	...	5 A
Number of inputs	2	...	3
Number of outputs	2	...	1
Connector type	screw terminals	...	screw terminals
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11g	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS 	...	<ul style="list-style-type: none"> The wBox free application on Android The wBox free application on iOS
Resolution	...	1920 x 1080 - 1080p @ HD-CVI / HD-TVI / AHD @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	...
Lens	...	2.8 mm	...
View angle	...	<ul style="list-style-type: none"> 102 ° (manufacturer data) 104 ° (our tests result) 	...
Range of IR illumination	...	40 m	...
White light LED illuminator range	...	40 m	...
IR illuminator power adjustment	...	Automatic	...

Main features	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • sunrise and sunset mode, • remote access, • voice control, • µWiFi technology support • Illuminated, color front panel with an additional control button 	...	<ul style="list-style-type: none"> • Electric strike control - relay contact, • Multiple users support from anywhere, • Control many objects from one app, • remote access, • voice control, • door control input, • µWiFi technology support • Additional security option by logging in with username and password
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Audio support via coaxial cable - HD-CVI only 	...
OSD menu	...	✓	...
Operation temp	-20 °C ... 50 °C	...	-20 °C ... 50 °C
Main features	...	<ul style="list-style-type: none"> • Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines 	...
Power supply	...	12 V DC / 350 mA	...
Power consumption	...	≤ 4.1 W	...
Housing	Plastic (ABS), DIN, TS-35 rail mounting	Dome, Metal	Plastic
Color	White	White	Black
"Index of Protection"	IP20	IP67	IP20
Vandal-proof	...	—	...
Operation temp	...	-40 °C ... 60 °C	...
Weight	0.062 kg	0.48 kg	0.036 kg

Dimensions	90 x 17.5 x 65 mm	Ø 106 x 99 mm	39 x 39 x 22 mm
Manufacturer / Brand	BleBox	DAHUA	BleBox
Guarantee	2 years	3 years	2 years