

	HUB USB 3.0 MH4PU-SV-BP	TV OR MONITOR MOUNT BS-106S	EXPANSION PLUG KS-10/6X120 KLIMAS	POE SWITCH WITH BUFFERED POWER SUPPLY IPUPS-5-11-F 5-PORT ATTE
				
	18.64 EUR 18.64 EUR	8.31 EUR 8.31 EUR	0.30 EUR 0.30 EUR	179.27 EUR 179.27 EUR
Mounting standard	...	VESA : 75, 100, 200, 400 x 200
Screen size range	...	23 " ... 42 "
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...
Connectors	<ul style="list-style-type: none"> 1 x plug - USB-A 4 x socket - USB-A
Bearing capacity	...	45 kg
Drilling diameter	10 mm	...
Length of the cable	150 cm
Distance from mounting surface	...	19 mm from wall
Expansion plug length	60 mm	...
USB standard	3.0
Color	...	Black
Tilt adjustment	...	—
LAN ports	<ul style="list-style-type: none"> 1 x RJ45 10/100 Base-T - Uplink, 5 x RJ45 10/100 Base-T + PoE (802.3af/at) / Passive PoE
Horizontal rotation	...	—
Screw dimensions	Ø 6 x 120 mm, SW-10	...
Housing	Aluminum + Plastic
Rotation in the plane of the screen	...	—
Management	—
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	...
LED diodes	AC, DC, CHARGING (battery charging), PoE
Transmission speed	<ul style="list-style-type: none"> 10 / 100 Mbps : 1 x Port Uplink, 10 / 100 Mbps : 5 x Port LAN & PoE
Maximal output power	<ul style="list-style-type: none"> 40 W @ Passive PoE - LAN1 ... LAN4 ports, 60 W @ Passive PoE - Port LAN5, 30 W @ PoE (802.3af/at) - LAN1 ... LAN5 ports
Maximal total power	60 W

Operation modes	<ul style="list-style-type: none"> • Standard : 100 m @ 10/100 Mb/s - LAN1 ... LAN6 ports • Long Range : 280 m @ 10 Mb/s - LAN1 ... LAN4 ports ; 100 m @ 10/100 Mb/s - LAN5, LAN6 ports
Main features	<ul style="list-style-type: none"> • Solid workmanship • Can be mounted on the edge of a tabletop or monitor frame using an integrated screw clamp 	<ul style="list-style-type: none"> • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 5 ports • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • Place for battery : 12 V / 18 Ah • Battery charging current : 1 A / 2 A - (set with the JP1 jumper) • Battery - Protection against reverse polarity connection, Protection against deep discharge of the battery • Technical outputs of the OC type signaling loss of voltage at the PSU output (OUF) and loss of voltage in the 230V mains (ACF) • PSU thermal protection : 130 °C • Overload protection • LAN & PoE ports - Short-circuit protection, Overvoltage • TAMPER switch indicating open the cover • "Index of Protection" : IP20
Power supply	190 ... 260 V AC
Weight	0.09 kg	1.45 kg	...	2.4 kg
Dimensions	89 x 46 x 23 mm	455 x 260 x 19 mm	...	325 x 305 x 100 mm
Manufacturer / Brand	ORICO	...	KLIMAS	ATTE
Guarantee	2 years	2 years	2 years	3 years