

	IP CAMERA T2A-PV Wi-Fi. Smart Dual Light Active Deterrence - 1080p 2.8 mm DAHUA	IP CAMERA TC-C32KN SPEC:I3/A/E/Y/2.8-12MM/V4.2 - 1080p 2.8 ... 12 mm TIANDY	IP CAMERA TC-C320N SPEC:I3/E/Y/2.8MM*P5 - 1080p 2.8 mm TIANDY
			
	41.00 EUR 41.00 EUR	160.83 EUR 160.83 EUR	188.24 EUR 188.24 EUR
In package	...	...	5 pcs The price for package
Standard	IP	IP	IP
Resolution	1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	1920 x 1080 - 1080p , 1280 x 720 - 720p	1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	1/3 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Lens	2.8 mm	2.8 ... 12 mm - Motozoom	2.8 mm
White light LED illuminator range	30 m	...	...
View angle	98 °	• 108 ° ... 31 ° (manufacturer data) • 98 ° ... 30 ° (our tests result)	• 100 ° (manufacturer data) • 93 ° (our tests result)
Range of IR illumination	30 m	30 m	30 m
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	Micro SD memory cards up to 512GB support (possible local recording)	—
Image compression method	H.265 / H.264 H.264B / H.264H	S+265 / H.265 / H.264	S+265 / H.265 / H.264
Alarm inputs / outputs	—	—	—
Audio	• Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support	• Microphone built-in • Audio transmission via network	• Microphone built-in • Audio transmission via network
Main stream frame rate	25 fps @ 1080p	25 fps @ 1080p	25 fps @ 2 Mpx
Max. number of on-line users	...	2	1
Interface	• Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45)	10/100 Base-TX (RJ-45)	10/100 Base-TX (RJ-45)
WEB Server	Built-in	Built-in	Built-in
ONVIF	✓	✓	✓
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Intelligent image analysis	Human detection	...	—
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	—
Default IP address	192.168.1.108	DHCP or 192.168.1.2	DHCP or 192.168.1.2
Default admin user / password	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777	80, 443, 3000, 3001, 3002, 23002	80
PC client access ports	37777	3000, 3001	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	37777	3000, 3001	---
Port ONVIF	80	80	80
Main features	• Active deterrence function • Smart Dual Light • Built-in hybrid illuminator (LED - IR/white) • Day/night mode • ICR - Movable InfraRed filter • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection	• WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Motion Detection • Privacy zones	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate • Privacy zones • Motion Detection
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	---	---
Power supply	12 V DC / 1 A (power adapter included)	• PoE (802.3af), • 12 V DC / 630 mA	PoE (802.3af)
Power consumption	max. 6.9 W	≤ 7 W	≤ 6 W
Housing	Dome - Plastic	Dome - Plastic	Dome - Metal + Plastic
Color	White	White	White
"Index of Protection"	IP67	IP66	—
Vandal-proof	---	—	---
Mechanical protection class	—	---	—
Operation temp	-40 °C ... 60 °C	-30 °C ... 60 °C	-30 °C ... 65 °C
Weight	0.34 kg	0.4 kg	0.23 kg
Dimensions	Ø 110 x 102 mm	Ø 120 x 96 mm	Ø 117 x 96 mm
Supported languages	Polish, English	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian	English
Manufacturer / Brand	DAHUA	TIANDY	TIANDY
Guarantee	3 years	3 years	3 years