




	POLE MOUNT CH-G	IP SPEED DOME CAMERA OUTDOOR IPC6312LR-AX4W-VG Wi-Fi, - 1080p 2.8 ... 12 mm UNIVIEW	POE SWITCH / EXTENDER PFT1300 3-PORT DAHUA
			
	12.27 EUR 12.27 EUR	370.09 EUR 370.09 EUR	23.29 EUR 23.29 EUR
Material	Steel galvanized
Standard	...	TCP/IP	...
Sensor	...	1/2.7 " Progressive Scan CMOS	...
Pole diameters range	Ø 30 ... Ø 120 mm
Matrix size	...	2.1 Mpx	...
Cable hiding	✓
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p	...
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)
Lens	...	2.8 ... 12 mm	...
Management	—
LED diodes	LAN, PoE
View angle	...	<ul style="list-style-type: none"> • 105 ° ... 29 ° (manufacturer data) • 83 ° ... 30 ° (our tests result) 	...
Transmission speed	10 / 100 Mbps
Optical zoom	...	x 4	...
Digital zoom	...	—	...
Range of IR illumination	...	50 m	...
Video output	...	—	...
Preset rotation speed	...	<ul style="list-style-type: none"> • 50 °/s (horizontal) • 40 °/s (vertical) 	...
Maximal output power	<ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade
Main features	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 50 °/s (horizontal), • 0.1 °/s ... 40 °/s (vertical) 	...
Range	100 m - Input 100 m - Output

Protections	Overvoltage
Horizontal rotation range	...	0 ° ... 345 ° - Rotation of the head is limited by stops	...
Vertical rotation range	...	-10 ° ... 110 °	...
RS-485 interface	...	—	...
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %
Number of presets	...	256	...
Horizontal scan	...	—	...
Route settings	...	16	...
Image compression method	...	Ultra H.265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	...	—	...
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Audio detection • Noise reduction 	...
Main stream frame rate	...	25 fps @ 1080p	...
Network interface	...	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz, IEEE 802.11 b/g/n, • 10/100 Base-TX (RJ-45) 	...
WEB Server	...	Built-in	...
Max. number of on-line users	...	32	...
ONVIF	...	✓	...
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView 	...
Default IP address	...	DHCP or 192.168.1.13	...
Default admin user / password	...	admin / 123456	...
Web browser access ports	...	80, 554	...
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	...	80	...
Port ONVIF	...	80	...
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...



Main features	...	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Support ARP defence • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • RESET button - on the cable • Privacy zones - max. 4 • Motion Detection • Tamper signaling • Image rotation and mirror • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • Home Position - set the camera to the specified position if no operator activity for a specified dwell time • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, face detection 	...
Housing	...	Speed Dome, Plastic	Plastic, DIN, TS-35 rail mounting
Color	Silver	White + Black	...
"Index of Protection"	...	IP66	...
Vandal-proof	...	—	...
Power supply	...	12 V DC / 1 A	PoE (802.3af/at)
Power consumption	...	≤ 12 W	0.3 W
Operation temp	...	-20 °C ... 60 °C	...
Weight	1.43 kg	0.85 kg	0.06 kg
Dimensions	...	Ø 133 x 185 x 276 mm (without bracket)	80 x 51 x 23 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	...
Manufacturer / Brand	...	UNIVIEW	DAHUA

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Guarantee	3 years	2 years	3 years
-----------	---------	---------	---------



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00