

	SINGLE SOCKET OUTLET SANTRA/4136-19/EPN 230 V 16 A IP44 Elektro-Plast	CONVERTER HDMI-OFT-20IR	EXTENDER HDMI+USB-EX-100
			
	5.04 USD 5.04 USD	178.51 USD 178.51 USD	111.99 USD 111.99 USD
Rated voltage	230 V / 50 Hz
Maximal current load	16 A
Grounding	✓
Cable terminals	screw terminals
Supported HDMI resolutions	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Socket type	CEE 7/5
Outputs	...	1 pcs LC 1 pcs JACK IR transmitter 1 pcs HDMI	...
Maximal transmission range	100 m UTP cat. 5e, 6
Protection shutter	—
Max. number of receivers working in the same time	253
Application	Santra product series
Protocols	HDbiT
Assembly	Claw or screw mounting
Inputs	...	1 pcs HDMI 1 pcs LC 1 pcs JACK IR receiver	...
Main features	<ul style="list-style-type: none"> • Extender also allows to extend an USB 2.0 port, eg. in order to control the recorder using the mouse • The devices do not require direct connection, they also operate via the LAN network • Audio transmission via network
"Index of Protection"	IP44
Main features	<ul style="list-style-type: none"> • Compliance with PN-EN-60669-1:2018-04 standard • Splash-proof casing 	...	<ul style="list-style-type: none"> • The need for a separate power supply for the transmitter and receiver
Housing	Plastic (ABS)
Color	Black
Power supply	2 x 5 V DC / 1 A (power adapter included)

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Supported HDMI input resolutions	...	480i @ 60Hz 480p @ 60Hz 576i @ 50Hz 576p @ 50Hz 720p @ 50/60Hz 1080i @ 50/60Hz 1080p @ 50/60Hz	...
Operation temp	-10 °C ... 60 °C
Permissible relative humidity	0 % ... 90 % (non-condensing)
Manufacturer / Brand	Elektro-Plast Nasielsk
Supported HDMI output resolutions	...	480p @ 60Hz 576p @ 50Hz 720p @ 50/60Hz 1080p @ 50/60Hz	...
Weight	0.088 kg	...	0.168 kg
Optical wavelength	...	• 1310 nm • 1550 nm	...
Connector type	...	LC	...
Fiber optic type	...	SMF 0-40km	...
Receiver sensitivity	...	≤ -32 dBm	...
Output power	...	≥ -11 dBm	...
Attenuation	...	≤ 14 dB	...
IR frequency	...	38 kHz	...
Dimensions	77 x 77 x 50 mm	138 x 79 x 25 mm	110 x 89 x 26 mm - Transmitter or receiver dimensions
Guarantee	7 years	2 years	2 years