



	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR DS-7104HQHI-K1(C)(S) 4 CHANNELS Hikvision	CUSTOMER PREMISES EQUIPMENT SXTSQ-5ACD MIKROTIK
		
	206.57 CAD 206.57 CAD	116.41 CAD 116.41 CAD
Frequency range	...	5150 MHz ... 5875 MHz
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Antenna type	...	16 dBi, 2Tx 2Rx MIMO - Bandwidth 5 GHz
Standards	...	IEEE 802.11 a/n/ac
Baud rates	...	1000 Mbps
LAN ports	...	1 x 10/100/1000 Mbps
Video inputs	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS	...
Vertical beam width (V)	...	23 °
Horizontal beam width (H)	...	23 °
Video outputs	1 pcs HDMI 1 pcs VGA	...
Audio inputs	<ul style="list-style-type: none"> • 1 pcs CINCH, • 4 Channels - Audio support via coaxial cable 	...
Audio outputs	1 pcs CINCH	...
Protections	...	Overvoltage protection
Transmitter power	...	25 dBm
Memory	...	256 MB RAM, 16 MB Flash
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Processor	...	IPQ-4018 4 x 716 MHz
Power supply PoE	...	✓
Power consumption	...	7 W
Operation temp	...	-40 °C ... 70 °C
Image records resolutions	<ul style="list-style-type: none"> • HD-TVI : 3.0 Mpx - 1920 x 1536, Channel 1 , • AHD / HD-CVI / HD-TVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 704 x 576 , • IP : max. 6 Mpx - 3072 x 2048 	...

Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps D1 @ 1 ... 25 fps for each channel	...
Operation modes	4 x HD-TVI / AHD / HD-CVI / CVBS / IP + 2 x IP	Client, WDS client, Router, Bridge (Point-to-Point) - 3 The level of license MikroTik RouterOS
Recording modes	Manual, Motion Detection, Schedule	...
Supported hard drives	1 x 6 TB SATA	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time	...
Network interface	1 x RJ-45 - 10/100 Base-TX	...
Bitrate	32 ... 6144 kbps	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect	...
Default admin user / password	admin / -	...
Default IP address	DHCP or 192.168.1.64	...
Web browser access ports	80	...
PC client access ports	554 RTSP, 8000	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream	...
Alarm inputs / outputs	—	...
PTZ control	Control compatible with coax HD-TVI Hikvision	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
USB	2 pcs USB 2.0	...
Mouse support	✓	...
IR remote controller in the set	—	...

Power supply	12 V DC / 1.5 A (power adapter included)	10 V ... 30 V DC PoE (power adapter included)
Color	White	...
Weight	0.49 kg	0.21 kg
Dimensions	210 x 200 x 47 mm	129 x 129 x 34 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	MikroTik
SAP Code	300226668	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00