



	NVR NVR501-08B-P8 8 CHANNELS, 8 PoE UNIVIEW	OVERVOLTAGE LIMITER AXON-PRO-IP-4POE+
		
	419.06 EUR 419.06 EUR	104.97 EUR 104.97 EUR
Number of channels	...	4
Standard	TCP/IP	...
Rated voltage	...	120 V
Maximal voltage	...	150 V
Supported resolutions	max. 8.3 Mpx 4K UHD - 3840 x 2160 px	...
Nominal current	...	600 mA
Video outputs	1 pcs HDMI 4K 1 pcs VGA	...
Voltage protection level line-PG [C2]	...	≤ 1000 V - 1.2/50 μs
Nominal discharge current line-PG [C2]	...	2 kA - 8/20 μs
Audio support	<ul style="list-style-type: none"> • 8 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Protected pairs of wires	...	1-2, 3-6, 4-5, 7-8
Audio inputs	1 pcs CINCH	...
Audio outputs	1 pcs CINCH	...
Connectors type	...	8 x RJ-45 shielded socket (4 Inputs, 4 Outputs)
Image compression method	Ultra 265 / H.265 / H.264	...
Bitrate	max. 80 Mbps	...
Length of grounding cable	...	0.52 m
Supported hard drives	1 x 8 TB SATA	...
Housing	...	Metal, black
Recording modes	Manual, Motion Detection, Schedule	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4/6/8/9 channel synchronous playback	...
Network interface	1 x RJ-45 10/100 Base-TX	...
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users	...

Network protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, RTSP	...
ONVIF	✓	...
Default IP address	DHCP or 192.168.1.30	...
Default admin user / password	admin / 123456	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation	...
Mobile client access ports	80	...
RTSP URL	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream	...
USB	1 x USB 2.0 1 x USB 3.0	...
Serial ports	—	...
Alarm inputs / outputs	—	...
PTZ control	PTZ Uniview cameras	...
Motion Detection	✓	...
Intelligent image analysis	✓	...
Main features	Functions implemented in cooperation between the recorder and cameras that support these functions • Intelligent image analysis : crossing the line (tripwire), intrusion, entering the marked area, leaving the marked area, scene changing, abandoned/missing object, objects tracking, people counting, crowd gathering estimation • Human detection • Audio detection • Support ANR function • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms	...
Mouse support	✓	...

IR remote controller in the set	—	...
Switch PoE	8-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)	...
Maximum total switch load	75 W	...
Power supply	52 V DC / 1.8 A (power adapter included)	...
Power consumption	max. 10 W (without HDD)	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.77 kg	0.33 kg
Dimensions	260 x 222 x 47 mm	167 x 50 x 32 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian	...
Manufacturer / Brand	UNIVIEW	...
Guarantee	3 years	2 years