







	<a href="#">MOUNTING SCREWS SM-6/RACK</a>	<a href="#">CAGE NUT ASSEMBLING TOOL SDMK-M5/M6 VALUE</a>	<a href="#">BLANK PANEL TO RACK CABINET Z19-2U-N</a>	<a href="#">ACCESS POINT 4G LTE +ROUTER RUT901 Dual SIM 2.4 GHz 300 Mbps Teltonika</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA DS-2CE56D8T-ITMF(2.8MM) - 1080p Hikvision</a>	<a href="#">AHD, HD-CVI, HD-TVI CAMERA APTI-H50PV21-28W 2Mpx / 5Mpx 2.8 mm</a>
						
	0.62 EUR 0.62 EUR	3.93 EUR 3.93 EUR	3.89 EUR 3.89 EUR	135.79 EUR 135.79 EUR	78.46 EUR 78.46 EUR	23.32 EUR 23.32 EUR
Width	...	...	19 "	...	...	...
Frequency range	...	...	...	2.4 GHz	...	...
Application	...	M5, M6	...	...	...	...
Application	Rack 19" / Rack 10"	...	...	...	...	...
Height	...	...	2 U	...	...	...
Standard	...	...	...	...	AHD / HD-CVI / HD-TVI / CVBS	AHD, HD-CVI, HD-TVI
Sensor	...	...	...	...	Progressive Scan CMOS	1/3 " Progressive Scan CMOS
Matrix size	...	...	...	...	2.1 Mpx	5 Mpx
Antenna type	...	...	...	2 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)	...	...
Package includes	• 4 x M6 screw, • 4 x cage nut, • 4 x plastic shoulder washer, which protects the varnish coating of panels from damage during tightening the screws	...	...	...	...	...
Material	Steel galvanized	Aluminum	Steel - powder painted	...	...	...
Standards	...	...	...	IEEE 802.11 b/g/n, 4G, 3G, 2G	...	...
Baud rates	...	...	...	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.236 Mbps (4G / 3G / 2G)	...	...
Resolution	...	...	...	...	• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI • 960 x 576 - 960H @ PAL	• 2592 x 1944 - 5 Mpx @ AHD, HD-TVI, • 2560 x 1440 - 3.7 Mpx @ AHD, HD-TVI, HD-CVI, • 1920 x 1080 - 1080p @ AHD, HD-CVI, HD-TVI
IR illuminator support	...	...	...	...	ICR - Movable InfraRed filter	...
Range of IR illumination	...	...	...	...	30 m	20 m
S/N ratio	...	...	...	...	> 62 dB	...
IR illuminator power adjustment	...	...	...	...	Automatic	Automatic
LAN ports	...	...	...	• 1 x 10/100 Mbps - WAN • 3 x 10/100 Mbps - LAN	...	...
Lens	...	...	...	...	2.8 mm	2.8 mm
View angle	...	...	...	...	• 104 ° (manufacturer data) • 101 ° (our tests result)	• 89 ° (manufacturer data) • 83 ° (our tests result)
Transmitter power	...	...	...	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM	...	...
Video output	...	...	...	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI - selectable by switch
LED indicators	...	...	...	Power, WAN, 3 x LAN, LTE, Signal indicator	...	...
Network type	...	...	...	4G, 3G	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	...	...	...	<ul style="list-style-type: none"> <li>• WDR ≥ 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• Sharpness - sharper image outlines</li> <li>• Auto White Balance</li> </ul>
OSD menu	...	...	...	...	OSD menu available via recorder	OSD menu available via recorder
Housing	...	...	...	...	Dome, Metal	Dome - Plastic
Color	...	Silver	Black	...	White	White
"Index of Protection"	...	...	...	...	IP67	—
Vandal-proof	...	...	...	...	—	—
Operation temp	...	...	...	...	-40 °C ... 60 °C	-20 °C ... 60 °C
SAP Code	...	...	...	...	300612680	...
LTE	...	...	...	✓	...	...
QSS	...	...	...	—	...	...
WDS	...	...	...	—	...	...
DHCP server	...	...	...	✓	...	...
Supported languages	...	...	...	...	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Protections	...	...	...	<ul style="list-style-type: none"> <li>• WPA-PSK/WPA2-PSK</li> <li>• WPA2-PSK</li> <li>• WPA2-EAP</li> <li>• WPA2-EAP/WPA3-EAP</li> <li>• WPA3-EAP</li> <li>• WPA2-PSK/WPA3-SAE</li> <li>• WPA3-SAE</li> <li>• OWE</li> <li>• AES-CCMP</li> <li>• TKIP</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>	...	...
Management interface	...	...	...	Web browser, Teltonika RMS application, SMS	...	...
Main features	...	<ul style="list-style-type: none"> <li>• Easy operation</li> <li>• Very easy and quick assembly</li> <li>• Reducing the risk of panel damage</li> <li>• Reduces risk of injury</li> </ul>	...	<ul style="list-style-type: none"> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Ability to work as a Hotspot,</li> <li>• Support for VoIP technology,</li> <li>• 2 x SIM socket</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul>	...	...
Power supply	...	...	...	<ul style="list-style-type: none"> <li>• 9 V DC / 1 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>	12 V DC / 280 mA	12 V DC / 180 mA
Power consumption	...	...	...	≤ 7 W	≤ 3.4 W	≤ 2.2 W
Operation temp	...	...	...	-40 °C ... 75 °C	...	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Permissible relative humidity	...	...	...	10 % ... 90 % (non-condensing)	...	...
Weight	0.037 kg	0.025 kg	0.39 kg	0.26 kg	0.24 kg	0.11 kg
Dimensions	• 19.9 mm - Total length • 13.5 mm - Thread length	75 x 40 x 14 mm	...	110 x 100 x 50 mm	91 x 83 x 68 mm	Ø 84 x 69 mm
Manufacturer / Brand	...	VALUE	...	Teltonika	Hikvision	APTI
Guarantee	2 years	2 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00